

ELECTRICAL CHARACTERISTICS

Part No.	Working Voltage (Vw)	Clamping Voltage (Vc)	ESD Withstanding	Capacitance (C)		Capacitance Tolerance
	Volts	Volts	Times	pF		%
	<15 μ A	1A,8/20 μ s	8KV*	1KHz	1MHz	
JMV0603C120T100	12	60	> 1000	-	10	\pm 20%

* - In system ESD withstanding pulse per IEC 61000-4-2, 8KV, contact discharge method.

Vw- The max. steady state DC operating voltage of which varistor could maintain also not exceeding 15uA leakage current.

Vc- The peak voltage acrossed the varistor measured at a specified pulse current and waveform.

C - The device capacitance measured with 1.0Vrms, 1KHz / 0.5rms, 1 I

MLV Storage condition \rightarrow Temperature: $\leq 30^{\circ}\text{C}$ / Humidity : $\leq 60\%$ RH (Moisture Sensitivity Levels: 2a)

MLV Preservation period \rightarrow 6 months

External Dimension

Chip Dimension

Chip Size	inch(mm)			
	L	W	T	A
0603 (1608)	0.063 \pm 0.006 (1.60 \pm 0.15)	0.031 \pm 0.006 (0.80 \pm 0.15)	0.035 max. (0.9max.)	0.014 \pm 0.006 (0.35 \pm 0.15)

