# **690D SERIES**

## **USB 3.0 TYPE-A RECEPTACLES - UPRIGHT RIGHT ANGLE PCB**

### **Features:**

- Up to 5 Gbps communication speed for standard USB 3.0
- Industry standard plug and play technology 'Hot Pluggable'
- Compatible with synchronous and asynchronous data transfer
- Data and power combined in one small package
- **RoHS compliant**



**USDC**#

VERSAL SERIAL BUS

# **Specifications:**

Insulator Material	Thermoplastic UL-94V-0	
Contact Material	Copper alloy	
Contact Plating	Nickel under plating with Gold plating on contact areas and Tin plating on tails	
Shell Material	Brass with Nickel plating	
Insertion Force	35N maximum	
Withdrawal Force	10N minimum	

### EXAMPLE PART NUMBER: 690D109-239-022

Series					
Connector Type					
Contact Plating Code					
Contact Code / Mounting Orientation					
Mounting Option					
Connector Option					
Material					
Insulator Color					

#### Sorios

Series:		Contact Code / Mounting Orientation:	
690D	Receptacle	3	Right Angle PCB (Perpendicular to PCB)
Connector Type:		Mounting Option:	
109	USB 3.0 Type-A	9	2 Tabs & 2 Boardlocks
Contact Plating:		Connector Option:	
1	$2\mu^{\prime\prime} \sim 5\mu^{\prime\prime}$ Gold	0	Tabs on Leading Edge of Shell
2	Gold Flash	2	No Tabs on Leading Edge of Shell - (Blue LCP Only)
3	$5\mu^{\prime\prime} \sim 10\mu^{\prime\prime}$ Gold	Material:	
5	15µ" Gold	1	LCP
6	30µ" Gold	2	PBT
		Insulator Color:	

1

2

Black

Blue

#### Ordering Code Notes:

Not all part numbers deriving from this ordering guide will be available.

Some may be available upon request. Please first consult the website, if the connector is not readily available then please contact EDAC's customer service for further inquiries.

