698C SERIES

USB TYPE-C RECEPTACLES - 24 PIN OPTION

Features:

- Up to 10 Gbps communication speed for USB 3.1 Type C
- Industry standard plug and play technology 'Hot Pluggable'
- Compatible with synchronous and asynchronous data transfer
- Data and power combined in one small package
- RoHS compliant



Specifications:

Insulator Material	Thermoplastic UL-94V-0	
Contact Material	Copper alloy	
Contact Plating	Nickel under plating with Gold plating on contact areas	
Shell Material	Stainless Steel with Nickel plating	
Insertion Force 5~20N		
Withdrawal Force	8~20N	

EXAMPLE PART NUMBER:	69	8C	124	-21	15	5-2	1	1
Series —								
Connector Type —————								
Contact Plating Code —————								
Contact Code / Mounting Orientation								
Mounting Option —————								
Connector Option —								
Material ————————————————————————————————————								
Insulator Color ———————————————————————————————————								

Series:	
698C	Receptacle
Connector Type:	
124	USB Type-C (24 Pin)
Contact Plating:	
2	Gold Flash
5	15μ" Gold
6	30μ" Gold

10	deri	ng C	code	N	otes:	

Options marked * are only available together.

Options marked ** are only available in part numbers $\,$ - 698C124-504-211 / 698C124-176-211

Not all part numbers deriving from this ordering guide will be available.

Some may be available upon request. Please first consult the website, if the connector is not readily available then please contact EDAC's customer service for further inquiries.

Contact Code /	Mounting	Orientation:
----------------	----------	--------------

Mid Mount PCB & SMT Mix * Vertical SMT ** **Mounting Option:** Plastic Posts & 4 Grounding Tabs - 4.0mm ± 0.25 Footprint ** Plastic Posts & 4 Grounding Tabs - 4.5mm \pm 0.25 Footprint * Plastic Posts & 4 Grounding Tabs - 5.0mm ± 0.25 Footprint Plastic Posts & 4 Grounding Tabs - 6.0mm ± 0.25 Footprint

Right Angle PCB & SMT Mix

Connector Option:

2 Standard - Flush or Mid-Mount to PCB

Material:

0

LCP

Insulator Color:

Black





