



Electrical specification:

- Insulation resistance: 500M Ω
- Dielectric withstanding voltage: 1000V AC
- DC current rating: 1.5A
- DC resistance: 0.1 Ω
- Contact resistance: 20m Ω

Physical specification:

- Coupler housing: polycarbonate resin high - impact UL94V-0 Thermoplastic
- Contact holder: ABS high - impact UL94V-0 Thermoplastic
- Spring wire: phosphor bronze 5100W temper wire, $\varnothing=0.45\text{mm}$, 3U AU / 30U
- PDNI over 60U nickel undercoat
- Insertion life: 750 mating cycles with standard compliant RJ45 plug
- Operating temperature: -10°C to 60°C
- Storage temperature range: -40°C to 68°C
- Humidity: 10%~90%RH

Standard Verification:

- ANSI/TIA-568-B.2-1 channel compliant
- ISO/IEC 11801 Class E channel compliant
- ISO/IEC 60603-7, UL 1863

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF MH CONNECTORS LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN	DATE
Johnny	09-18-12
APPROVED	DATE

SCALE	SHEET	OF	REV:
	1	OF 1	1.0
DRAWING No			
39-763631142			

RJ45 UNSHIELDED COUPLER PANEL
MOUNTED CAT6 OFFSET PIN BLACK.



THIS SERIES FULLY CONFORMS TO THE
EUROPEAN UNION DIRECTIVES 2002/95/EC
AND 2002/96/EC FOR RoHS COMPLIANCY.

