


- Plug-in unit
- Fixed output voltages
- Thermal fuse in transformer and thermal protection in the regulator
- Exchangeable output plugs
- Plugg-inn enhet
- Faste utgangsspenninger
- Termosikring i transformator og termisk beskyttelse i regulator
- Utskiftbare plugger



Technical specifications	Tekniske data	
Input voltage:	Inngangsspenning:	230 VAC +6/-10%, 50/60Hz
Output voltage:	Utgangsspenning:	5-24 VDC
Max. output power:	Maks. utgangseffekt:	4,8 W
Ripple:	Rippel:	< 30 mV p-p
Insulation class:	Isolasjonsklasse:	II
Electrical safety standard:	Elektrisk sikkerhetsstandard:	EN 60065, EN 60950
EMC standards	EMC standarder	
• Emission:	• Emisjon:	EN 61000-6-3
• Immunity:	• Immunitet:	EN 61000-6-1
Output terminals	Utgangsterminaler	
Cord with/without plug:	Sek. ledning med/uten plugg:	Accessories /Tilbehør
Dimensions excl. plug (LxWxH):	Mål uten plugg (LxBxH):	95 x 51 x 57 mm
Weight:	Vekt:	420 g

Voltage version (VDC) Spenningsversjoner (VDC)	Nominal load (mA) Merkelast (mA)
5	700
6	600
7,5	600
9	500
12	400
15	340
18	280
24	210