



**3V 512M-BIT SERIAL SLC NAND FLASH MEMORY WITH DUAL/QUAD SPI BUFFER READ & CONTINUOUS READ** 

> Publication Release Date: April 26, 2021 Revision F



2.       FEATURES       6         3.       PACKAGE TYPES AND PIN CONFIGURATIONS       7         3.1       Pad Configuration WSON 6x5-mm / 8x6-mm       7         3.2       Pad Description WSON 6x5-mm / 8x6-mm       7         3.3       Pin Configuration SOIC 300-mil       8         3.4       Pin Description SOIC 300-mil       8         3.5       Ball Configuration TFBGA 8x6-mm (5x5 Ball Array)       9         3.6       Ball Description TFBGA 8x6-mm       9         4.       PIN DESCRIPTIONS       10         4.1       Chip Select (/CS)       10         4.2       Serial Data Input, Output and IOs (DI, DO and IOO, IO1, IO2, IO3)       10         4.3       Write Protect (WP)       10         4.4       HOLD (/HOLD)       10       10         4.5       Serial Clock (CLK)       10         5       BLOCK DIAGRAM       11         6.1       Device Operation Flow       12         6.1.1       Standard SPI Instructions       12         6.1.2       Dual SPI Instructions       13         6.2       Write Protection       14         7       PROTECTION, CONFIGURATION AND STATUS REGISTERS       15         7.1       Protecti	1.	GENE	ERAL DESCRIPTIONS								
3.1       Pad Configuration WSON 6x5-mm / 8x6-mm       7         3.2       Pad Description WSON 6x5-mm / 8x6-mm       7         3.3       Pin Configuration SOIC 300-mil       8         3.4       Pin Description SOIC 300-mil       8         3.5       Ball Configuration TFBGA 8x6-mm (5x5 Ball Array)       9         3.6       Ball Description TFBGA 8x6-mm       9         4.       PIN DESCRIPTIONS       10         4.1       Chip Select (/CS)       10         4.2       Serial Data Input, Output and IOs (DI, DO and IO0, IO1, IO2, IO3)       10         4.3       Write Protect (WP)       10         4.4       HOLD (/HOLD)       10         4.5       Serial Clock (CLK)       10         4.5       Serial Clock (CLK)       10         4.5       Serial Clock (CLK)       10         5.       BLOCK DIAGRAM       11         6.       FUNCTIONAL DESCRIPTIONS       12         6.1       Device Operation Flow       12         6.1.1       Standard SPI Instructions       12         6.1.2       Dual SPI Instructions       13         6.1.4       Hold Function       13         6.2       Write Protection       14	2.	FEATU	URES								
3.2       Pad Description WSON 6x5-mm / 8x6-mm.	3.	PACK	ACKAGE TYPES AND PIN CONFIGURATIONS								
3.2       Pad Description WSON 6x5-mm / 8x6-mm.		3.1									
3.4       Pin Description SOIC 300-mil.       8         3.5       Ball Configuration TFBGA 8x6-mm (5x5 Ball Array)       9         3.6       Ball Description TFBGA 8x6-mm		3.2									
3.5       Ball Configuration TFBGA 8x6-mm (5x5 Ball Array)       9         3.6       Ball Description TFBGA 8x6-mm       9         4.       PIN DESCRIPTIONS.       10         4.1       Chip Select (/CS)       10         4.2       Serial Data Input, Output and IOs (DI, DO and IO0, IO1, IO2, IO3)       10         4.3       Write Protect (/WP)       10         4.4       HOLD (/HOLD)       10         4.5       Serial Clock (CLK)       10         5.       BLOCK DIAGRAM       11         6.       FUNCTIONAL DESCRIPTIONS       12         6.1       Device Operation Flow       12         6.1.1       Standard SPI Instructions       12         6.1.2       Dual SPI Instructions       12         6.1.3       Quad SPI Instructions       13         6.1.4       Hold Function       13         6.2       Write Protection       14         7.       PROTECTION, CONFIGURATION AND STATUS REGISTERS.       15         7.1       Protection Register / Status Register-1 (Volatile Writable, OTP lockable)       15         7.1.1       Block Protect Bits (BP3, BP2, BP1, BP0, TB) – Volatile Writable, OTP lockable       16         7.1.2       Write Protection Enable Bit (WP-E) – Volatile W		3.3	Pin C	onfiguration SOIC 300-mil	8						
3.6       Ball Description TFBGA 8x6-mm       9         4.       PIN DESCRIPTIONS       10         4.1       Chip Select (/CS)       10         4.2       Serial Data Input, Output and IOs (DI, DO and IO0, IO1, IO2, IO3)       10         4.3       Write Protect (/WP)       10         4.4       HOLD (/HOLD)       10         4.5       Serial Clock (CLK)       10         5.       BLOCK DIAGRAM       11         6.       FUNCTIONAL DESCRIPTIONS       12         6.1.1       Standard SPI Instructions       12         6.1.2       Dual SPI Instructions       12         6.1.3       Quad SPI Instructions       13         6.1.4       Hold Function       13         6.1.3       Quad SPI Instructions       13         6.1.4       Hold Function       13         6.1.5       Write Protection       14         7.       PROTECTION, CONFIGURATION AND STATUS REGISTERS       15         7.1       Protection Register / Status Register-1 (Volatile Writable, OTP lockable)       15         7.1.2       Write Protection Enable Bit (WP-E) – Volatile Writable, OTP lockable       16         7.1.2       Write Protect Bits (BP3, BP2, BP1, BP0, TB) – Volatile Writable, OTP lockable		3.4	Pin D	escription SOIC 300-mil	8						
4.       PIN DESCRIPTIONS       10         4.1       Chip Select (/CS)       10         4.2       Serial Data Input, Output and IOs (DI, DO and IO0, IO1, IO2, IO3)       10         4.3       Write Protect (WP)       10         4.4       HOLD (/HOLD)       10         4.5       Serial Clock (CLK)       10         5.       BLOCK DIAGRAM       11         6.       FUNCTIONAL DESCRIPTIONS       12         6.1       Device Operation Flow       12         6.1.1       Standard SPI Instructions       12         6.1.2       Dual SPI Instructions       12         6.1.3       Quad SPI Instructions       13         6.2       Write Protection       13         6.2       Write Protection       14         7.       PROTECTION, CONFIGURATION AND STATUS REGISTERS       15         7.1       Protection Register / Status Register-1 (Volatile Writable, OTP lockable)       15         7.1.1       Block Protect Bits (BP3, BP2, BP1, BP0, TB) – Volatile Writable, OTP lockable       16         7.1.2       Write Protection Enable Bit (WP-E) – Volatile Writable, OTP lockable       16         7.1.2       Write Protect Bits (SRP1, SRP0) – Volatile Writable, OTP lockable       17         7.2.1 <td></td> <td>3.5</td> <td></td> <td>•</td> <td></td>		3.5		•							
4.1       Chip Select (/CS)       10         4.2       Serial Data Input, Output and IOs (DI, DO and IOO, IO1, IO2, IO3)       10         4.3       Write Protect (/WP)       10         4.4       HOLD (/HOLD)       10         4.5       Serial Clock (CLK)       10         5.       BLOCK DIAGRAM       11         6.       FUNCTIONAL DESCRIPTIONS       12         6.1       Device Operation Flow       12         6.1.1       Standard SPI Instructions       12         6.1.2       Dual SPI Instructions       12         6.1.3       Quad SPI Instructions       12         6.1.4       Hold Function       13         7.1       PROTECTION, CONFIGURATION AND STATUS REGISTERS       15         7.1.1       Block Protect Bits (BP3, BP2, BP1, BP0, TB) – Volatile Writable, OTP lockable       15         7.1.2       Write Protection Enable Bit (WP-E) – Volatile Writable, OTP lockable       16         7.2       Configuratio		3.6	Ball D	Description TFBGA 8x6-mm	9						
4.2       Serial Data Input, Output and IOs (DI, DO and IO0, IO1, IO2, IO3)       10         4.3       Write Protect (/WP)       10         4.4       HOLD (/HOLD)       10         4.5       Serial Clock (CLK)       10         5.       BLOCK DIAGRAM       11         6.       FUNCTIONAL DESCRIPTIONS       12         6.1       Device Operation Flow       12         6.1.1       Standard SPI Instructions       12         6.1.2       Dual SPI Instructions       12         6.1.3       Quad SPI Instructions       12         6.1.4       Hold Function       13         6.2       Write Protection       14         7.       PROTECTION, CONFIGURATION AND STATUS REGISTERS       15         7.1       Protection Register / Status Register-1 (Volatile Writable, OTP lockable)       15         7.1.1       Block Protect Bits (BP3, BP2, BP1, BP0, TB) – Volatile Writable, OTP lockable       16         7.1.2       Write Protection Enable Bit (WP-E) – Volatile Writable, OTP lockable       16	4.	PIN DE	ESCRI	PTIONS	10						
4.3       Write Protect (/WP)       10         4.4       HOLD (/HOLD)       10         4.5       Serial Clock (CLK)       10         5.       BLOCK DIAGRAM       11         6.       FUNCTIONAL DESCRIPTIONS       12         6.1       Device Operation Flow       12         6.1.1       Standard SPI Instructions       12         6.1.2       Dual SPI Instructions       12         6.1.3       Quad SPI Instructions       12         6.1.4       Hold Function       13         6.2       Write Protection       14         7.       PROTECTION, CONFIGURATION AND STATUS REGISTERS       15         7.1       Protection Register / Status Register-1 (Volatile Writable, OTP lockable)       15         7.1.1       Block Protect Bits (BP3, BP2, BP1, BP0, TB) – Volatile Writable, OTP lockable       15         7.1.2       Write Protection Enable Bit (WP-E) – Volatile Writable, OTP lockable       16         7.1.3       Status Register Protect Bits (SRP1, SRP0) – Volatile Writable, OTP lockable       17         7.2.1       One Time Program Lock Bit (OTP-L) – OTP lockable       17         7.2.2       Enter OTP Access Mode Bit (OTP-E) – Volatile Writable       17         7.2.3       Status Register-1 Lock Bit (SR1-L) – OTP		4.1	Chip \$	Select (/CS)	10						
4.3       Write Protect (/WP)       10         4.4       HOLD (/HOLD)       10         4.5       Serial Clock (CLK)       10         5.       BLOCK DIAGRAM       11         6.       FUNCTIONAL DESCRIPTIONS       12         6.1       Device Operation Flow       12         6.1.1       Standard SPI Instructions       12         6.1.2       Dual SPI Instructions       12         6.1.3       Quad SPI Instructions       12         6.1.4       Hold Function       13         6.2       Write Protection       14         7.       PROTECTION, CONFIGURATION AND STATUS REGISTERS       15         7.1       Protection Register / Status Register-1 (Volatile Writable, OTP lockable)       15         7.1.1       Block Protect Bits (BP3, BP2, BP1, BP0, TB) – Volatile Writable, OTP lockable       15         7.1.2       Write Protection Enable Bit (WP-E) – Volatile Writable, OTP lockable       16         7.1.3       Status Register Protect Bits (SRP1, SRP0) – Volatile Writable, OTP lockable       17         7.2.1       One Time Program Lock Bit (OTP-L) – OTP lockable       17         7.2.2       Enter OTP Access Mode Bit (OTP-E) – Volatile Writable       17         7.2.3       Status Register-1 Lock Bit (SR1-L) – OTP		4.2	•								
<ul> <li>4.4 HOLD (/HOLD)</li> <li>4.5 Serial Clock (CLK)</li> <li>10</li> <li>5. BLOCK DIAGRAM</li> <li>11</li> <li>6. FUNCTIONAL DESCRIPTIONS</li> <li>6.1 Device Operation Flow</li> <li>6.1 Device Operation Flow</li> <li>6.1.1 Standard SPI Instructions</li> <li>6.1.2 Dual SPI Instructions</li> <li>6.1.3 Quad SPI Instructions</li> <li>6.1.4 Hold Function</li> <li>6.2 Write Protection</li> <li>14</li> <li>7. PROTECTION, CONFIGURATION AND STATUS REGISTERS</li> <li>7.1 Protection Register / Status Register-1 (Volatile Writable, OTP lockable)</li> <li>15</li> <li>7.1.1 Block Protect Bits (BP3, BP2, BP1, BP0, TB) – Volatile Writable, OTP lockable</li> <li>15</li> <li>7.1.2 Write Protection Enable Bit (WP-E) – Volatile Writable, OTP lockable</li> <li>16</li> <li>7.2 Configuration Register / Status Register-2 (Volatile Writable, OTP lockable</li> <li>17</li> <li>7.2.1 One Time Program Lock Bit (OTP-L) – OTP lockable</li> <li>17</li> <li>7.2.3 Status Register-1 Lock Bit (SR1-L) – OTP lockable</li> <li>17</li> <li>7.2.4 ECC Enable Bit (ECC-E) – Volatile Writable</li> </ul>		4.3									
<ul> <li>5. BLOCK DIAGRAM.</li> <li>FUNCTIONAL DESCRIPTIONS.</li> <li>6.1 Device Operation Flow</li> <li>6.1 Device Operation Flow</li> <li>6.1 Device Operation Flow</li> <li>6.1 Device Operation Section</li> <li>6.1 Device Operation Flow</li> <li>6.1 Device Operation Section Section Section Section Flow</li> <li>7.1 Protection Register / Status Register-1 (Volatile Writable, OTP lockable)</li> <li>7.1 Device Flow Flow</li> <li>7.2 Configuration Register / Status Register-2 (Volatile Writable, OTP lockable)</li> <li>7.2 Configuration Register / Status Register-2 (Volatile Writable)</li> <li>7.2.1 One Time Program Lock Bit (OTP-L) – OTP lockable</li> <li>7.2.2 Enter OTP Access Mode Bit (OTP-E) – Volatile Writable</li> <li>7.2.3 Status Register-1 Lock Bit (SR1-L) – OTP lockable</li> <li>17</li> <li>7.2.4 ECC Enable Bit (ECC-E) – Volatile Writable</li> </ul>		4.4									
<ul> <li>FUNCTIONAL DESCRIPTIONS</li></ul>		4.5	Serial	Clock (CLK)	10						
6.1       Device Operation Flow       12         6.1.1       Standard SPI Instructions       12         6.1.2       Dual SPI Instructions       12         6.1.3       Quad SPI Instructions       13         6.1.4       Hold Function       13         6.2       Write Protection       14         7.       PROTECTION, CONFIGURATION AND STATUS REGISTERS       15         7.1       Protection Register / Status Register-1 (Volatile Writable, OTP lockable)       15         7.1.1       Block Protect Bits (BP3, BP2, BP1, BP0, TB) – Volatile Writable, OTP lockable       15         7.1.2       Write Protection Enable Bit (WP-E) – Volatile Writable, OTP lockable       16         7.1.3       Status Register Protect Bits (SRP1, SRP0) – Volatile Writable, OTP lockable       16         7.2.1       One Time Program Lock Bit (OTP-L) – OTP lockable       17         7.2.2       Enter OTP Access Mode Bit (OTP-E) – Volatile Writable       17         7.2.3       Status Register-1 Lock Bit (SR1-L) – OTP lockable       17         7.2.4       ECC Enable Bit (ECC-E) – Volatile Writable       18	5.	BLOCI	K DIAG	RAM	11						
6.1.1       Standard SPI Instructions       12         6.1.2       Dual SPI Instructions       12         6.1.3       Quad SPI Instructions       13         6.1.4       Hold Function       13         6.2       Write Protection       14         7.       PROTECTION, CONFIGURATION AND STATUS REGISTERS       15         7.1       Protection Register / Status Register-1 (Volatile Writable, OTP lockable)       15         7.1.1       Block Protect Bits (BP3, BP2, BP1, BP0, TB) – Volatile Writable, OTP lockable       15         7.1.2       Write Protection Enable Bit (WP-E) – Volatile Writable, OTP lockable       16         7.1.3       Status Register Protect Bits (SRP1, SRP0) – Volatile Writable, OTP lockable       16         7.2.1       One Time Program Lock Bit (OTP-L) – OTP lockable       17         7.2.2       Enter OTP Access Mode Bit (OTP-E) – Volatile Writable       17         7.2.3       Status Register-1 Lock Bit (SR1-L) – OTP lockable       17         7.2.4       ECC Enable Bit (ECC-E) – Volatile Writable       18	6.	FUNC									
6.1.2       Dual SPI Instructions       12         6.1.3       Quad SPI Instructions       13         6.1.4       Hold Function       13         6.2       Write Protection       14         7.       PROTECTION, CONFIGURATION AND STATUS REGISTERS       15         7.1       Protection Register / Status Register-1 (Volatile Writable, OTP lockable)       15         7.1.1       Block Protect Bits (BP3, BP2, BP1, BP0, TB) – Volatile Writable, OTP lockable       16         7.1.2       Write Protection Enable Bit (WP-E) – Volatile Writable, OTP lockable       16         7.1.3       Status Register Protect Bits (SRP1, SRP0) – Volatile Writable, OTP lockable       16         7.2       Configuration Register / Status Register-2 (Volatile Writable)       17         7.2.1       One Time Program Lock Bit (OTP-L) – OTP lockable       17         7.2.2       Enter OTP Access Mode Bit (OTP-E) – Volatile Writable       17         7.2.3       Status Register-1 Lock Bit (SR1-L) – OTP lockable       17         7.2.4       ECC Enable Bit (ECC-E) – Volatile Writable       18		6.1	Devic	e Operation Flow	12						
6.1.3       Quad SPI Instructions       13         6.1.4       Hold Function       13         6.2       Write Protection       14         7.       PROTECTION, CONFIGURATION AND STATUS REGISTERS       15         7.1       Protection Register / Status Register-1 (Volatile Writable, OTP lockable)       15         7.1.1       Block Protect Bits (BP3, BP2, BP1, BP0, TB) – Volatile Writable, OTP lockable       16         7.1.2       Write Protection Enable Bit (WP-E) – Volatile Writable, OTP lockable       16         7.1.3       Status Register Protect Bits (SRP1, SRP0) – Volatile Writable, OTP lockable       16         7.2       Configuration Register / Status Register-2 (Volatile Writable)       17         7.2.1       One Time Program Lock Bit (OTP-L) – OTP lockable       17         7.2.2       Enter OTP Access Mode Bit (OTP-E) – Volatile Writable       17         7.2.3       Status Register-1 Lock Bit (SR1-L) – OTP lockable       17         7.2.4       ECC Enable Bit (ECC-E) – Volatile Writable       18			6.1.1	Standard SPI Instructions	12						
6.1.4       Hold Function			6.1.2	Dual SPI Instructions	12						
<ul> <li>6.2 Write Protection</li></ul>			6.1.3	Quad SPI Instructions	13						
<ul> <li>7. PROTECTION, CONFIGURATION AND STATUS REGISTERS</li></ul>			6.1.4	Hold Function	13						
<ul> <li>7.1 Protection Register / Status Register-1 (Volatile Writable, OTP lockable)</li></ul>		6.2	Write	Protection	14						
<ul> <li>7.1.1 Block Protect Bits (BP3, BP2, BP1, BP0, TB) – Volatile Writable, OTP lockable</li></ul>	7.	PROT	ECTIO	N, CONFIGURATION AND STATUS REGISTERS	15						
<ul> <li>7.1.2 Write Protection Enable Bit (WP-E) – Volatile Writable, OTP lockable</li></ul>		7.1	Prote	ction Register / Status Register-1 (Volatile Writable, OTP lockable)	15						
7.1.3       Status Register Protect Bits (SRP1, SRP0) – Volatile Writable, OTP lockable			7.1.1	Block Protect Bits (BP3, BP2, BP1, BP0, TB) - Volatile Writable, OTP lockable	15						
<ul> <li>7.2 Configuration Register / Status Register-2 (Volatile Writable)</li></ul>			7.1.2	Write Protection Enable Bit (WP-E) – Volatile Writable, OTP lockable	16						
<ul> <li>7.2.1 One Time Program Lock Bit (OTP-L) – OTP lockable</li></ul>			-								
<ul> <li>7.2.2 Enter OTP Access Mode Bit (OTP-E) – Volatile Writable</li></ul>		7.2	Config								
<ul> <li>7.2.3 Status Register-1 Lock Bit (SR1-L) – OTP lockable</li></ul>			7.2.1								
7.2.4 ECC Enable Bit (ECC-E) – Volatile Writable			7.2.2								
			-								
7.2.5 Buffer Read / Continuous Read Mode Bit (BUF) – <i>Volatile Writable</i>											
7.2.6 Output Driver Strength (ODS-1, ODS-0) – <i>Volatile Writable</i>											
7.2.7 Hold Disable (H-DIS) - <i>Volatile Writable</i>		7.0									
7.3 Status Register-3 (Status Only)		7.3									
7.3.1 Look-Up Table Full (LUT-F) – <i>Status Only</i>											
<ul> <li>7.3.2 Cumulative ECC Status (ECC-1, ECC-0) – <i>Status Only</i></li></ul>											
7.3.4 Erase Failure (E-FAIL) – <i>Status Only</i>											
7.3.4       Elase Failule (E-FAIL) – Status Only         7.3.5       Write Enable Latch (WEL) – Status Only											

		es winbond	
		7.3.6 Erase/Program In Progress (BUSY) – Status Only	21
		7.3.7 Reserved Bits – Non Functional	21
	7.4	W25N512GV Status Register Memory Protection	22
8.	INSTF	RUCTIONS	23
	8.1	Device ID and Instruction Set Tables	23
		8.1.1 Manufacturer and Device Identification	23
		8.1.2 Instruction Set Table 1 (Continuous Read, BUF = 0, xxT Default Power Up Mode) <sup>(11)</sup>	24
		8.1.3 Instruction Set Table 2 (Buffer Read, BUF = 1, xxG Default Power Up Mode) <sup>(12)</sup>	25
		8.1.4 Instruction Set Table 3 (Buffer Read, BUF = 1 Fixed, xxR) <sup>(12)</sup>	26
	8.2	Instruction Descriptions	28
		8.2.1 Device Reset (FFh), Enable Reset (66h) and Reset Device (99h)	28
		8.2.2 Read JEDEC ID (9Fh)	30
		8.2.3 Read Status Register (0Fh / 05h)	31
		8.2.4 Write Status Register (1Fh / 01h)	32
		8.2.5 Write Enable (06h)	
		8.2.6 Write Disable (04h)	
		8.2.7 Bad Block Management (A1h)	
		8.2.8 Read BBM Look Up Table (A5h)	
		8.2.9 Last ECC Failure Page Address (A9h)	
		8.2.10 128KB Block Erase (D8h)	
		8.2.11 Load Program Data (02h) / Random Load Program Data (84h)	
		8.2.12 Quad Load Program Data (32h) / Quad Random Load Program Data (34h)	
		8.2.13 Program Execute (10h)	
		8.2.14 Page Data Read (13h)	
		8.2.15 Read Data (03h)	
		8.2.16 Fast Read (0Bh)	
		8.2.17 Fast Read with 4-Byte Address (0Ch)	
		8.2.18 Fast Read Dual Output (3Bh)	
		<ul><li>8.2.19 Fast Read Dual Output with 4-Byte Address (3Ch)</li><li>8.2.20 Fast Read Quad Output (6Bh)</li></ul>	
		8.2.21 Fast Read Quad Output (661)	
		8.2.22 Fast Read Quad Output with 4-Byte Address (och)	
		8.2.23 Fast Read Dual I/O (BBI)	
		8.2.24 Fast Read Quad I/O (EBh)	
		8.2.25 Fast Read Quad I/O with 4-Byte Address (ECh)	
		8.2.26 Accessing Unique ID / Parameter / OTP Pages (OTP-E=1)	
		8.2.27 Parameter Page Data Definitions	
		8.2.28 Deep Power-Down (B9h)	
		8.2.29 Release Power-Down (ABh)	
		8.2.30 Chip Erase (C7h / 60h)	
9.	ELEC	TRICAL CHARACTERISTICS <sup>0</sup>	
0.	9.1	Absolute Maximum Ratings <sup>(1)</sup>	
	9.1 9.2	Operating Ranges	
	9.2 9.3	Power-up Power-down Timing Requirements	
	9.4	DC Electrical Characteristics	oz

		winbond se	
	9.5	AC Measurement Conditions	
	9.6	AC Electrical Characteristics <sup>(3)</sup>	64
	9.7	Serial Output Timing	66
	9.8	Serial Input Timing	66
	9.9	/HOLD Timing	66
	9.10	/WP Timing	66
10.	INVAL	ID BLOCK MANAGEMENT	67
	10.1	Invalid blocks	67
	10.2	Initial invalid blocks	67
	10.3	Error in Operation	68
	10.4	Addressing in Program Operation	68
11.	PACK	AGE SPECIFICATIONS	69
	11.1	8-Pad WSON 6x5-mm (Package Code P)	69
	11.2	8-Pad WSON 8x6-mm (Package Code E)	
	11.3	16-Pin SOIC 300-mil (Package Code F)	
	11.4	24-Ball TFBGA 8x6-mm (Package Code B, 5x5-1 Ball Array)	72
12.	ORDE	RING INFORMATION	73
	12.1	Valid Part Numbers and Top Side Marking	74
13.	REVIS		

Figure 1a. W25N512GV Pad Assignments, 8-pad WSON 6x5-mm / 8x6-mm (Package Code P, E)	7
Figure 1b. W25N512GV Pin Assignments, 16-pin SOIC 300-mil (Package Code F)	8
Figure 1c. W25N512GV Ball Assignments, 24-ball TFBGA 8x6-mm (Package Code B)	9
Figure 2. W25N512GV Flash Memory Architecture and Addressing	.11
Figure 3. W25N512GV Flash Memory Operation Diagram	.12
Figure 4a. Protection Register / Status Register-1 (Address Axh)	. 15
Figure 4b. Configuration Register / Status Register-2 (Address Bxh)	. 17
Figure 4c. Status Register-3 (Address Cxh)	.20
Figure 5a. Device Reset Instruction	. 28
Figure 5b. Enable Reset and Reset Instruction Sequence	.28
Figure 6. Read JEDEC ID Instruction	. 30
Figure 7. Read Status Register Instruction	. 31
Figure 8. Write Status Register-1/2/3 Instruction	. 32
Figure 9. Write Enable Instruction	. 33
Figure 10. Write Disable Instruction	. 33
Figure 11. Bad Block Management Instruction	. 34
Figure 12. Read BBM Look Up Table Instruction	
Figure 13. Last ECC Failure Page Address Instruction	. 36
Figure 14. 128KB Block Erase Instruction	. 37
Figure 15. Load / Random Load Program Data Instruction	. 38
Figure 16. Quad Load / Quad Random Load Program Data Instruction	. 39
Figure 17. Program Execute Instruction	
Figure 18. Page Data Read Instruction	.41
Figure 19a. Read Data Instruction (Buffer Read Mode, BUF=1)	.42
Figure 19b. Read Data Instruction (Continuous Read Mode, BUF=0)	
Figure 20a. Fast Read Instruction (Buffer Read Mode, BUF=1)	
Figure 20b. Fast Read Instruction (Continuous Read Mode, BUF=0)	.43
Figure 21a. Fast Read with 4-Byte Address Instruction (Buffer Read Mode, BUF=1)	.44
Figure 21b. Fast Read with 4-Byte Address Instruction (Continuous Read Mode, BUF=0)	.44
Figure 22a. Fast Read Dual Output Instruction (Buffer Read Mode, BUF=1)	. 45
Figure 22b. Fast Read Dual Output Instruction (Continuous Read Mode, BUF=0)	. 45
Figure 23a. Fast Read Dual Output with 4-Byte Address Instruction (Buffer Read Mode, BUF=1)	.46
Figure 23b. Fast Read Dual Output with 4-Byte Address Instruction (Continuous Read Mode, BUF=0).	.46
Figure 24a. Fast Read Quad Output Instruction (Buffer Read Mode, BUF=1)	. 47
Figure 24b. Fast Read Quad Output Instruction (Continuous Read Mode, BUF=0)	. 47
Figure 25a. Fast Read Quad Output with 4-Byte Address Instruction (Buffer Read Mode, BUF=1)	. 48
Figure 25b. Fast Read Quad Output with 4-Byte Address Instruction (Continuous Read Mode, BUF=0)	. 48
Figure 26a. Fast Read Dual I/O Instruction (Buffer Read Mode, BUF=1)	.49
Figure 26b. Fast Read Dual I/O Instruction (Continuous Read Mode, BUF=0)	.49
Figure 27a. Fast Read Dual I/O with 4-Byte Address Instruction (Buffer Read Mode, BUF=1)	. 50
Figure 27b. Fast Read Dual I/O with 4-Byte Address Instruction (Continuous Read Mode, BUF=0)	. 50

<b>T</b>	
Figure 28a. Fast Read Quad I/O Instruction (Buffer Read Mode, BUF=1)	51
Figure 28b. Fast Read Quad I/O Instruction (Continuous Read Mode, BUF=0)	52
Figure 29a. Fast Read Quad I/O with 4-Byte Address Instruction (Buffer Read Mode, BUF=1)	53
Figure 29b. Fast Read Quad I/O with 4-Byte Address Instruction (Continuous Read Mode, BUF=0)	54
Figure 30. Deep Power-Down Instruction	57
Figure 31. Release Power-down Instruction	58
Figure 32. Chip Erase Instruction	59
Figure 33a. Power-up Power-down Timing and Voltage Levels	61
Figure 33b. Power-up, Power-Down Requirement	61
Figure 34. AC Measurement I/O Waveform	63
Figure 35. Flow chart of create initial invalid block table	67

**FEES winbond** 

## 1. GENERAL DESCRIPTIONS

The W25N512GV (512M-bit) Serial SLC NAND Flash Memory provides a storage solution for systems with limited space, pins and power. The W25N SpiFlash family incorporates the popular SPI interface and the traditional large NAND non-volatile memory space. They are ideal for code shadowing to RAM, executing code directly from Dual/Quad SPI (XIP) and storing voice, text and data. The device operates on a single 2.7V to 3.6V power supply with current consumption as low as 25mA active, 10µA for standby and 1µA for deep power down. All W25N SpiFlash family devices are offered in space-saving packages which were impossible to use in the past for the typical NAND flash memory.

The W25N512GV 512M-bit memory array is organized into 32,768 programmable pages of 2,048-bytes each. The entire page can be programmed at one time using the data from the 2,048-Byte internal buffer. Pages can be erased in groups of 64 (128KB block erase). The W25N512GV has 512 erasable blocks.

The W25N512GV supports the standard Serial Peripheral Interface (SPI), Dual/Quad I/O SPI: Serial Clock, Chip Select, Serial Data I/O0 (DI), I/O1 (DO), I/O2 (/WP), and I/O3 (/HOLD). SPI clock frequencies of up to 166MHz are supported allowing equivalent clock rates of 332MHz (166MHz x 2) for Dual I/O and 664MHz (166MHz x 4) for Quad I/O when using the Fast Read Dual/Quad I/O instructions.

The W25N512GV provides a new Continuous Read Mode that allows for efficient access to the entire memory array with a single Read command. This feature is ideal for code shadowing applications.

A Hold pin, Write Protect pin and programmable write protection, provide further control flexibility. Additionally, the device supports JEDEC standard manufacturer and device ID, Unique ID page, Parameter page and ten 2,048-Byte OTP pages. To provide better NAND flash memory manageability, user configurable internal ECC, bad block management are also available in W25N512GV.

## 2. FEATURES

#### • New W25N Family of SpiFlash Memories

- -W25N512GV: 512M-bit / 64M-Byte
- Standard SPI: CLK, /CS, DI, DO, /WP, /Hold
- Dual SPI: CLK, /CS, IO<sub>0</sub>, IO<sub>1</sub>, /WP, /Hold
- Quad SPI: CLK, /CS, IO<sub>0</sub>, IO<sub>1</sub>, IO<sub>2</sub>, IO<sub>3</sub>
- Compatible SPI serial flash commands
- Highest Performance Serial NAND Flash
  - 166MHz Standard/Dual/Quad SPI clocks
- 332/664MHz equivalent Dual/Quad SPI
- 50MB/S continuous data transfer rate
- Fast Program/Erase performance
- 100,000 erase/program cycles<sup>(5)</sup>
- 10-year data retention

#### • Efficient "Continuous Read Mode"<sup>(1)</sup>

- Alternative method to the Buffer Read Mode
- No need to issue "Page Data Read" between Read commands
- Allows direct read access to the entire array

### Low Power, Wide Temperature Range

- Single 2.7 to 3.6V supply
- 25mA active, 10µA standby, 1µA DPD<sup>(4)</sup>
- -40°C to +85/105°C operating range
- Flexible Architecture with 128KB blocks – Uniform 128K-Byte Block Erase
- Flexible page data load methods

#### Advanced Features

- On chip 1-Bit ECC for memory array
- ECC status bits indicate ECC results
- bad block management and LUT<sup>(2)</sup> access
- Software and Hardware Write-Protect
- Power Supply Lock-Down and OTP protection
- Unique ID and Parameter pages<sup>(6)</sup>
- Ten 2KB OTP pages<sup>(3)</sup>

#### Space Efficient Packaging

- 8-pad WSON 6x5-mm
- 8-pad WSON 8x6-mm
- 16-pin SOIC 300-mil
- 24-ball TFBGA 8x6-mm
- Contact Winbond for other package options

Notes:

- Only the Read command structures are different between the "Continuous Read Mode (BUF=0)" and the "Buffer Read Mode (BUF=1)", all other commands are identical. W25N512GVxxG/R: Default BUF=1 after power up W25N512GVxxT: Default BUF=0 after power up
- 2. LUT stands for Look-Up Table.
- 3. OTP pages can only be programmed.
- 4. DPD stands for Deep Power Down.
- 5. Endurance specification is based on the on-chip ECC or 1bit/528 byte ECC(Error Correcting Code)
- 6. Please refer to Section 8.2.26 and 8.2.27 for more detail

## 3. PACKAGE TYPES AND PIN CONFIGURATIONS

W25N512GV is offered in an 8-pad WSON 6x5-mm (package code P), 8x6-mm (package code E), a 16pin SOIC 300-mil (package code F) and two 24-ball 8x6-mm TFBGA (package code B) packages as shown in Figure 1a-c respectively. Package diagrams and dimensions are illustrated at the end of this datasheet.

### 3.1 Pad Configuration WSON 6x5-mm / 8x6-mm




Figure 1a. W25N512GV Pad Assignments, 8-pad WSON 6x5-mm / 8x6-mm (Package Code P, E)

## 3.2 Pad Description WSON 6x5-mm / 8x6-mm

PAD NO.	PAD NAME	I/O	FUNCTION		
1	/CS	I	Chip Select Input		
2	DO (IO1)	I/O	Data Output (Data Input Output 1) <sup>(1)</sup>		
3	/WP (IO2)	I/O	Write Protect Input ( Data Input Output 2) <sup>(2)</sup>		
4	GND		Ground		
5	DI (IO0)	I/O	Data Input (Data Input Output 0) <sup>(1)</sup>		
6	CLK	I	Serial Clock Input		
7	/HOLD (IO3)	I/O	Hold Input (Data Input Output 3) <sup>(2)</sup>		
8	VCC		Power Supply		

Notes:

1. IO0 and IO1 are used for Standard and Dual SPI instructions

2. IO0 – IO3 are used for Quad SPI instructions, /WP & /HOLD functions are only available for Standard/Dual SPI.

winbond

## 3.3 Pin Configuration SOIC 300-mil




Figure 1b. W25N512GV Pin Assignments, 16-pin SOIC 300-mil (Package Code F)

### 3.4 Pin Description SOIC 300-mil

PIN NO.	PIN NAME	I/O	FUNCTION		
1	/HOLD (IO3)	I/O	Hold Input (Data Input Output 3) <sup>(2)</sup>		
2	VCC		Power Supply		
3	N/C		No Connect		
4	N/C		No Connect		
5	N/C		No Connect		
6	N/C		No Connect		
7	/CS	I	Chip Select Input		
8	DO (IO1)	I/O	Data Output (Data Input Output 1) <sup>(1)</sup>		
9	/WP (IO2)	I/O	Write Protect Input (Data Input Output 2) <sup>(2)</sup>		
10	GND		Ground		
11	N/C		No Connect		
12	N/C		No Connect		
13	N/C		No Connect		
14	N/C		No Connect		
15	DI (IO0)	I/O	Data Input (Data Input Output 0) <sup>(1)</sup>		
16	CLK	I	Serial Clock Input		

#### Notes:

1. IO0 and IO1 are used for Standard and Dual SPI instructions

2. IO0 - IO3 are used for Quad SPI instructions, /WP & /HOLD functions are only available for Standard/Dual SPI.



## 3.5 Ball Configuration TFBGA 8x6-mm (5x5 Ball Array)

	То	p Vie	w	
	)			
	A2 NC	(Å3) NC	(Á4) NC	(Å5) ≥0
(BT) NC		(B3) GND	(B4) VCC	(85) NC
(C) NC		C3) NC	(C4) /WP (IO <sub>2</sub> )	ĆŚ) NC
D) NC		(10 <sub>0</sub> )	(D4) /HOLD(IO3) /RESET	D5) NC
E) NC		€3) NC	(E4) NC	(£5) NC
	Packa	age Co	ode B	

Figure 1c. W25N512GV Ball Assignments, 24-ball TFBGA 8x6-mm (Package Code B)

## 3.6 Ball Description TFBGA 8x6-mm

BALL NO.	PIN NAME	I/O	FUNCTION		
B2	CLK	Ι	Serial Clock Input		
B3	GND		Ground		
B4	VCC		Power Supply		
C2	/CS	Ι	Chip Select Input		
C4	/WP (IO2)	I/O	Write Protect Input (Data Input Output 2) <sup>(2)</sup>		
D2	DO (IO1)	I/O	Data Output (Data Input Output 1) <sup>(1)</sup>		
D3	DI (IO0)	I/O	Data Input (Data Input Output 0) <sup>(1)</sup>		
D4	/HOLD (IO3)	I/O	Hold Input (Data Input Output 3) <sup>(2)</sup>		
Multiple	NC		No Connect		

#### Notes:

1. IO0 and IO1 are used for Standard and Dual SPI instructions

2. IO0 - IO3 are used for Quad SPI instructions, /WP & /HOLD functions are only available for Standard/Dual SPI.

winbond

4. PIN DESCRIPTIONS

## 4.1 Chip Select (/CS)

The SPI Chip Select (/CS) pin enables and disables device operation. When /CS is high the device is deselected and the Serial Data Output (DO, or IO0, IO1, IO2, IO3) pins are at high impedance. When deselected, the devices power consumption will be at standby levels unless an internal erase, program or write status register cycle is in progress. When /CS is brought low the device will be selected, power consumption will increase to active levels and instructions can be written to and data read from the device. After power-up, /CS must transition from high to low before a new instruction will be accepted. The /CS input must track the VCC supply level at power-up and power-down (see "Write Protection" and Figure 33b). If needed, a pull-up resistor on the /CS pin can be used to accomplish this.

## 4.2 Serial Data Input, Output and IOs (DI, DO and IO0, IO1, IO2, IO3)

The W25N512GV supports standard SPI, Dual SPI and Quad SPI operation. Standard SPI instructions use the unidirectional DI (input) pin to serially write instructions, addresses or data to the device on the rising edge of the Serial Clock (CLK) input pin. Standard SPI also uses the unidirectional DO (output) to read data or status from the device on the falling edge of CLK.

Dual and Quad SPI instructions use the bidirectional IO pins to serially write instructions, addresses or data to the device on the rising edge of CLK and read data or status from the device on the falling edge of CLK.

## 4.3 Write Protect (/WP)

The Write Protect (/WP) pin can be used to prevent the Status Register from being written. Used in conjunction with the Status Register's Block Protect bits BP[3:0] and Status Register Protect SRP bits SRP[1:0], a portion as small as one 128KB Block or up to the entire memory array can be hardware protected. The WP-E bit in the Protection Register (SR-1) controls the functions of the /WP pin.

When WP-E=0, the device is in the Software Protection mode that only SR-1 can be protected. The /WP pin functions as a data I/O pin for the Quad SPI operations, as well as an active low input pin for the Write Protection function for SR-1. Refer to section 7.1.3 for detail information.

When WP-E=1, the device is in the Hardware Protection mode that /WP becomes a dedicated active low input pin for the Write Protection of the entire device. If /WP is tied to GND, all "Write/Program/Erase" functions are disabled. The entire device (including all registers, memory array, OTP pages) will become read-only. Quad SPI read operations are also disabled when WP-E is set to 1.


### 4.4 HOLD (/HOLD)

During Standard and Dual SPI operations, the /HOLD pin allows the device to be paused while it is actively selected. When /HOLD is brought low, while /CS is low, the DO pin will be at high impedance and signals on the DI and CLK pins will be ignored (don't care). When /HOLD is brought high, device operation can resume. The /HOLD function can be useful when multiple devices are sharing the same SPI signals. The /HOLD pin is active low.

When a Quad SPI Read/Buffer Load command is issued, /HOLD pin will become a data I/O pin for the Quad operations and no HOLD function is available until the current Quad operation finishes. /HOLD (IO3) must be driven high by the host, or an external pull-up resistor must be placed on the PCB, in order to avoid allowing the /HOLD input to float.

## 4.5 Serial Clock (CLK)

The SPI Serial Clock Input (CLK) pin provides the timing for serial input and output operations. ("See SPI Operations")



31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0 Address Bits SpiFlash (up to 128M-Bit) X X 64KB Block Addr (256 Blocks) Page Address (256 Pages) Byte Address (0-255 Byte) Х x x x x x 64KB Block Address Page Address (256 Pages) Byte Address (0-255 Byte) SpiFlash (up to 32G-Bit) 
 X
 X
 X
 X

 X
 X
 X
 X
 X
 Column Address (CA) [11:0] Page Address (PA) [14:0] Serial NAND (512M-Bit) 128KB Block Addr (1024 Blocks) Page Addr (64 Pages) Ext Byte Address (0-2047 Byte) Main Memory Array (2,048-Byte) ECC Protected Spare Area (64-Byte) Page Sector 0 Sector 1 Sector 2 Sector 3 Spare 0 Spare 1 Spare 2 Spare 3 Structure 512-Byte 512-Byte 512-Byte 512-Byte 16-Byte 16-Byte 16-Byte 16-Byte (2.112-Byte)

Block (64 Pages, 64 X 2KB)

64 X

64B




Figure 2. W25N512GV Flash Memory Architecture and Addressing

## W25N512GVxxG/T/R 6. FUNCTIONAL DESCRIPTIONS

## 6.1 Device Operation Flow




Figure 3. W25N512GV Flash Memory Operation Diagram

## 6.1.1 Standard SPI Instructions

The W25N512GV is accessed through an SPI compatible bus consisting of four signals: Serial Clock (CLK), Chip Select (/CS), Serial Data Input (DI) and Serial Data Output (DO). Standard SPI instructions use the DI input pin to serially write instructions, addresses or data to the device on the rising edge of CLK. The DO output pin is used to read data or status from the device on the falling edge of CLK.

SPI bus operation Mode 0 (0,0) and 3 (1,1) are supported. The primary difference between Mode 0 and Mode 3 concerns the normal state of the CLK signal when the SPI bus master is in standby and data is not being transferred to the Serial Flash. For Mode 0, the CLK signal is normally low on the falling and rising edges of /CS. For Mode 3, the CLK signal is normally high on the falling and rising edges of /CS.

## 6.1.2 Dual SPI Instructions

The W25N512GV supports Dual SPI operation when using instructions such as "Fast Read Dual Output (3Bh)" and "Fast Read Dual I/O (BBh)". These instructions allow data to be transferred to or from the device at two to three times the rate of ordinary Serial Flash devices. The Dual SPI Read instructions are ideal for quickly downloading code to RAM upon power-up (code-shadowing) or for executing non-speed-critical

code directly from the SPI bus (XIP). When using Dual SPI instructions, the DI and DO pins become bidirectional I/O pins: IO0 and IO1.

#### 6.1.3 Quad SPI Instructions

The W25N512GV supports Quad SPI operation when using instructions such as "Fast Read Quad Output (6Bh/6Ch)", "Fast Read Quad I/O (EBh/ECh)" and "Quad Program Data Load (32h/34h)". These instructions allow data to be transferred to or from the device four to six times the rate of ordinary Serial Flash. The Quad Read instructions offer a significant improvement in continuous and random access transfer rates allowing fast code-shadowing to RAM or execution directly from the SPI bus (XIP). When using Quad SPI instructions the DI and DO pins become bidirectional IO0 and IO1, and the /WP and /HOLD pins become IO2 and IO3 respectively.

#### 6.1.4 Hold Function

For Standard SPI and Dual SPI operations, the /HOLD signal allows the W25N512GV operation to be paused while it is actively selected (when /CS is low). The /HOLD function may be useful in cases where the SPI data and clock signals are shared with other devices. For example, consider if the page buffer was only partially written when a priority interrupt requires use of the SPI bus. In this case the /HOLD function can save the state of the instruction and the data in the buffer so programming can resume where it left off once the bus is available again. The /HOLD function is only available for standard SPI and Dual SPI operation, not during Quad SPI. When a Quad SPI command is issued, /HOLD pin will act as a dedicated IO pin (IO3).

To initiate a /HOLD condition, the device must be selected with /CS low. A /HOLD condition will activate on the falling edge of the /HOLD signal if the CLK signal is already low. If the CLK is not already low the /HOLD condition will activate after the next falling edge of CLK. The /HOLD condition will terminate on the rising edge of the /HOLD signal if the CLK signal is already low. If the CLK is not already low the /HOLD condition will terminate on the rising edge of the /HOLD signal if the CLK signal is already low. If the CLK is not already low the /HOLD condition will terminate after the next falling edge of CLK. During a /HOLD condition, the Serial Data Output (DO) is high impedance, and Serial Data Input (DI) and Serial Clock (CLK) are ignored. The Chip Select (/CS) signal should be kept active (low) for the full duration of the /HOLD operation to avoid resetting the internal logic state of the device.

### 6.2 Write Protection

Applications that use non-volatile memory must take into consideration the possibility of noise and other adverse system conditions that may compromise data integrity. To address this concern, the W25N512GV provides several means to protect the data from inadvertent writes.

winbond

- Device resets when VCC is below threshold
- Write enable/disable instructions and automatic write disable after erase or program
- Software and Hardware (/WP pin) write protection using Protection Register (SR-1)
- Lock Down write protection for Protection Register (SR-1) until the next power-up
- One Time Program (OTP) write protection for memory array using Protection Register (SR-1)
- Hardware write protection using /WP pin when WP-E is set to 1

Upon power-up or at power-down, while VCC is below VCC(min), (See "Power-up Power-down Timing Requirements"), all operations are disabled and no instructions are recognized. During power-up, after the VCC voltage exceeds VCC(min) and tVSL has elapsed, all program and erase related instructions are further disabled for a time delay of tPUW. This includes the Write Enable, Program Execute, Block Erase and the Write Status Register instructions. Note that the chip select pin (/CS) must track the VCC supply level at power-up until the VCC-min level and tVSL time delay is reached, and it must also track the VCC supply level at power-down to prevent adverse command sequence. If needed a pull-up resister on /CS can be used to accomplish this.

After power-up the device is automatically placed in a write-disabled state with the Status Register Write Enable Latch (WEL) set to a 0. A Write Enable instruction must be issued before a Program Execute, Block Erase, Chip Erase or Bad Block Management instruction will be accepted. After completing a program or erase instruction the Write Enable Latch (WEL) is automatically cleared to a write-disabled state of 0.

Software controlled write protection is facilitated using the Write Status Register instruction and setting the Status Register Protect (SRP0, SRP1) and Block Protect (TB, BP[3:0]) bits. These settings allow a portion or the entire memory array to be configured as read only. Used in conjunction with the Write Protect (/WP) pin, changes to the Status Register can be enabled or disabled under hardware control. See Protection Register section for further information.

The WP-E bit in Protection Register (SR-1) is used to enable the hardware protection. When WP-E is set to 1, bringing /WP low in the system will block any Write/Program/Erase command to the W25N512GV, the device will become read-only. The Quad SPI operations are also disabled when WP-E is set to 1.



## 7. PROTECTION, CONFIGURATION AND STATUS REGISTERS

Three Status Registers are provided for W25N512GV: Protection Register (SR-1), Configuration Register (SR-2) & Status Register (SR-3). Each register is accessed by Read Status Register and Write Status Register commands combined with 1-Byte Register Address respectively.

The Read Status Register instruction (05h / 0Fh) can be used to provide status on the availability of the flash memory array, whether the device is write enabled or disabled, the state of write protection, Read modes, Protection Register/OTP area lock status, Erase/Program results, ECC usage/status. The Write Status Register instruction can be used to configure the device write protection features, Software/Hardware write protection, Read modes, enable/disable ECC, Protection Register/OTP area lock. Write access to the Status Register is controlled by the state of the non-volatile Status Register Protect bits (SRP0, SRP1), the Write Enable instruction, and when WP-E is set to 1, the /WP pin.

#### S7 S6 S5 **S**4 S3 S2 **S**1 S0 SRP0 BP3 BP2 BP1 BP0 TB WP-E SRP1 Status Register Protect-0 (Volatile Writable, OTP Lock) **Block Protect Bits** (Volatile Writable, OTP Lock) **Top/Bottom Protect Bit** (Volatile Writable, OTP Lock) /WP Enable Bit (Volatile Writable, OTP Lock) Status Register Protect-1 (Volatile Writable, OTP Lock)

## 7.1 Protection Register / Status Register-1 (Volatile Writable, OTP lockable)

Figure 4a. Protection Register / Status Register-1 (Address Axh)

## 7.1.1 Block Protect Bits (BP3, BP2, BP1, BP0, TB) - Volatile Writable, OTP lockable

The Block Protect bits (BP3, BP2, BP1, BP0 & TB) are volatile read/write bits in the status register-1 (S6, S5, S4, S3 & S2) that provide Write Protection control and status. Block Protect bits can be set using the Write Status Register Instruction. All, none or a portion of the memory array can be protected from Program and Erase instructions (see Status Register Memory Protection table). The default values for the Block Protection bits are 1 after power up to protect the entire array. If the SR1-L bit in the Configuration Register (SR-2) is set to 1, the default values will the values that are OTP locked.

**\_\_\_** winbond **\_\_** 

## 7.1.2 Write Protection Enable Bit (WP-E) - Volatile Writable, OTP lockable

The Write Protection Enable bit (WP-E) is a volatile read/write bits in the status register-1 (S1). The WP-E bit, in conjunction with SRP1 & SRP0, controls the method of write protection: software protection, hardware protection, power supply lock-down or one time programmable (OTP) protection, /WP pin functionality, and Quad SPI operation enable/disable. When WP-E = 0 (default value), the device is in Software Protection mode, /WP & /HOLD pins are multiplexed as IO pins, and Quad program/read functions are enabled all the time. When WP-E is set to 1, the device is in Hardware Protection mode, all Quad functions are disabled and /WP & /HOLD pins become dedicated control input pins.

### 7.1.3 Status Register Protect Bits (SRP1, SRP0) - Volatile Writable, OTP lockable

The Status Register Protect bits (SRP1 and SRP0) are volatile read/write bits in the status register (S0 and S7). The SRP bits control the method of write protection: software protection, hardware protection, power supply lock-down or one time programmable (OTP) protection.

	Software Protection (Driven by Controller, Quad Program/Read is enabled)									
SRP1         SRP0         WP-E         /WP / IO2         Descriptions										
0	0	0	Х	No /WP functionality /WP pin will always function as IO2						
0	1	0	0	SR-1 cannot be changed (/WP = 0 during Write Status) /WP pin will function as IO2 for Quad operations						
0	1	0	1	SR-1 can be changed (/WP = 1 during Write Status) /WP pin will function as IO2 for Quad operations						
1	0	0	Х	Power Lock Down <sup>(1)</sup> SR-1 /WP pin will always function as IO2						
1	1	0	Х	Enter OTP mode to protect SR-1 (allow SR1-L=1) /WP pin will always function as IO2						

	Hardware Protection (System Circuit / PCB layout, Quad Program/Read is disabled)									
SRP1         SRP0         WP-E         /WP only         Descriptions										
0	Х	1	VCC	SR-1 can be changed						
1	0	1	VCC	Power Lock-Down <sup>(1)</sup> SR-1						
1	1	1	VCC	Enter OTP mode to protect SR-1 (allow SR1-L=1)						
х	х	1	GND	All "Write/Program/Erase" commands are blocked Entire device (SRs, Array, OTP area) is read-only						

Notes:

1. When SRP1, SRP0 = (1, 0), a power-down, power-up cycle will change SRP1, SRP0 to (0, 0) state.






Figure 4b. Configuration Register / Status Register-2 (Address Bxh)

#### 7.2.1 One Time Program Lock Bit (OTP-L) – OTP lockable

In addition to the main memory array, W25N512GV also provides an OTP area for the system to store critical data that cannot be changed once it's locked. The OTP area consists of 10 pages of 2,112-Byte each. The default data in the OTP area are FFh. Only Program command can be issued to the OTP area to change the data from "1" to "0", and data is not reversible ("0" to "1") by the Erase command. Once the correct data is programmed in and verified, the system developer can set OTP-L bit to 1, so that the entire OTP area will be locked to prevent further alteration to the data.

#### 7.2.2 Enter OTP Access Mode Bit (OTP-E) – Volatile Writable

The OTP-E bit must be set to 1 in order to use the standard Program/Read commands to access the OTP area as well as to read the Unique ID / Parameter Page information. The default value after power up or a RESET command is 0.

#### 7.2.3 Status Register-1 Lock Bit (SR1-L) – OTP lockable

The SR1-L lock bit is used to OTP lock the values in the Protection Register (SR-1). Depending on the settings in the SR-1, the device can be configured to have a portion of or up to the entire array to be write-protected, and the setting can be OTP locked by setting SR1-L bit to 1. SR1-L bit can only be set to 1 permanently when SRP1 & SRP0 are set to (1,1), and OTP Access Mode must be entered (OTP-E=1) to execute the programming. Please refer to 8.2.26 for detailed information.


**\_\_\_** winbond **\_\_** 

## 7.2.4 ECC Enable Bit (ECC-E) – Volatile Writable

W25N512GV has a built-in ECC algorithm that can be used to preserve the data integrity. Internal ECC calculation is done during page programming, and the result is stored in the extra 64-Byte area for each page. During the data read operation, ECC engine will verify the data values according to the previously stored ECC information and to make necessary corrections if needed. The verification and correction status is indicated by the ECC Status Bits. ECC function is enabled by default when power on (ECC-E=1), and it will not be reset to 0 by the Device Reset command.

The constraint when ECC-E=1 are as follows:

- The areas protected by ECC is shown in the table below. User Data I is protected by ECC, but User Data II is out of protected by ECC.
- The Number of Partial Page Program (NoP) is 4 for the entire page, including the spare area. Therefore the user needs to program one sector and optionally User Data 1 of pared spare area (example, main area-sector 0 and spare area-spare 0) at one time program to properly and automatically program the ECC parity code.



Notes:

- 1. UD2: User Data II
- 2. UD1: User Data I
- 3. EPC: ECC parity code

The gray area of the above table is protected by ECC

## **Example 1**

## 7.2.5 Buffer Read / Continuous Read Mode Bit (BUF) - Volatile Writable

W25N512GV provides two different modes for read operations, Buffer Read Mode (BUF=1) and Continuous Read Mode (BUF=0). Prior to any Read operation, a Page Data Read command is needed to initiate the data transfer from a specified page in the memory array to the Data Buffer. By default, after power up, the data in page 0 will be automatically loaded into the Data Buffer and the device is ready to accept any read commands.

The Buffer Read Mode (BUF=1) requires a Column Address to start outputting the existing data inside the Data Buffer, and once it reaches the end of the data buffer (Byte 2,111), DO (IO1) pin will become high-Z state.

The Continuous Read Mode (BUF=0) doesn't require the starting Column Address. The device will always start output the data from the first column (Byte 0) of the Data buffer, and once the end of the data buffer (Byte 2,047) is reached, the data output will continue through the next memory page. With Continuous Read Mode, it is possible to read out the entire memory array using a single read command. Please refer to respective command descriptions for the dummy cycle requirements for each read commands under different read modes.

For W25N512GVxxG part number, the default value of BUF bit after power up is 1. BUF bit can be written to 0 in the Status Register-2 to perform the Continuous Read operation.

For W25N512GVxxT part number, the default value of BUF bit after power up is 0. BUF bit can be written to 1 in the Status Register-2 to perform the Buffer Read operation.

For W25N01GVxxxR part number, the default value of BUF bit is fixed as 1. BUF bit can't be written to 0 in the Status Register-2.

BUF	ECC-E	Read Mode (Starting from Buffer)	ECC Status	Data Output Structure
1	0	Buffer Read	N/A	2,048 + 64
1	1	Buffer Read	Page based	2,048 + 64
0	0	Continuous Read	N/A	2,048
0	1	Continuous Read	Operation based	2,048

#### 7.2.6 Output Driver Strength (ODS-1, ODS-0) - Volatile Writable

ODS-1, ODS-0	Output Driver Strength
0, 0	100%
0, 1	75%
1, 0	50% (default)
1, 1	25%

#### 7.2.7 Hold Disable (H-DIS) - Volatile Writable

When the Hold Disable (H-DIS) bit set to 1, the hold function would be disabled. If the user wants to use the hold function, the H-DIS bit has to be set 0.



## 7.3 Status Register-3 (Status Only)




Figure 4c. Status Register-3 (Address Cxh)

## 7.3.1 Look-Up Table Full (LUT-F) - Status Only

To facilitate the NAND flash memory bad block management, the W25N512GV is equipped with an internal Bad Block Management Look-Up-Table (BBM LUT). Up to 10 bad memory blocks may be replaced by a good memory block respectively. The addresses of the blocks are stored in the internal Look-Up Table as Logical Block Address (LBA, the bad block) & Physical Block Address (PBA, the good block). The LUT-F bit indicates whether the 10 memory block links have been fully utilized or not. The default value of LUT-F is 0, once all 10 links are used, LUT-F will become 1, and no more memory block links may be established.

### 7.3.2 Cumulative ECC Status (ECC-1, ECC-0) - Status Only

ECC function is used in NAND flash memory to correct limited memory errors during read operations. The ECC Status Bits (ECC-1, ECC-0) should be checked after the completion of a Read operation to verify the data integrity. The ECC Status bits values are don't care if ECC-E=0. These bits will be cleared to 0 after a power cycle or a RESET command or a Page Data Read command.

ECC S	Status	Descriptions
ECC-1	ECC-0	Descriptions
0	0	The entire data output is provided without requiring any ECC correction
0	1	The entire data output experienced an 1 bit correction event after reading either single or multiple pages.
1	0	The entire data output experienced a 2 bit error event in a single page that cannot be corrected <sup>2</sup> in the Continuous Read Mode, an additional command can be used to read out the Page Address (PA) that contains the error.
1	1	The entire data output experienced a 2 bit error event in multiple pages. In the Continuous Read Mode, the additional command can only provide the last Page Address (PA) that contain the 2 bit error. PAs for other pages with the 2 bit error is not available. The data read is not suitable for use <sup>2,3</sup> .





#### Notes:

- As the ECC engine is based on Hamming code, the ECC status bits are applicable for 1 bit ECC correction and 2 bit ECC detection. This Serial NAND is not expected to experience 3 or more bits of error when used within the datasheet specifications. When there is a 1 bit error correction event, user may decide to erase and reprogram the associated block, based on the user's quality policy.
- 2. If the read operation contains both 1 or 2 bit error event, the 2 bit error condition will be used.
- 3. ECC-1, ECC-0 = (1, 1) is only applicable during Continuous Read operation (BUF=0).

#### 7.3.3 Program Failure (P-FAIL) – Status Only

The Program Failure Bit is used to indicate whether the internally-controlled Program operation was executed successfully (P-FAIL=0) or timed out (P-FAIL=1). The P-FAIL bit is also set when the Program command is issued to a locked or protected memory array or OTP area. This bit is cleared at the beginning of the Program Execute instruction on an unprotected memory array or OTP area. Device Reset instruction can also clear the P-FAIL bit.

#### 7.3.4 Erase Failure (E-FAIL) - Status Only

The Erase Failure Bit is used to indicate whether the internally-controlled Erase operation was executed successfully (E-FAIL=0) or timed out (E-FAIL=1). The E-FAIL bit is also set when the Erase command is issued to a locked or protected memory array. This bit is cleared at the beginning of the Block Erase instruction on an unprotected memory array. Device Reset instruction can also clear the E-FAIL bit.

#### 7.3.5 Write Enable Latch (WEL) - Status Only

Write Enable Latch (WEL) is a read only bit in the status register (S1) that is set to 1 after executing a Write Enable Instruction. The WEL status bit is cleared to 0 when the device is write disabled. A write disable state occurs upon power-up or after any of the following instructions: Write Disable, Program Execute, Block/Chip Erase, Page Data Read, Program Execute and Bad Block Management for OTP pages.

#### 7.3.6 Erase/Program In Progress (BUSY) - Status Only

BUSY is a read only bit in the status register (S0) that is set to a 1 state when the device is powering up or executing a Page Data Read, Bad Block Management, Program Execute, Block/Chip Erase, Program Execute for OTP area, OTP Locking or after a Continuous Read instruction. During this time the device will ignore further instructions except for the Read Status Register and Read JEDEC ID instructions. When the program, erase or write status register instruction has completed, the BUSY bit will be cleared to a 0 state indicating the device is ready for further instructions.

#### 7.3.7 Reserved Bits - Non Functional

There are a few reserved Status Register bits that may be read out as a "0" or "1". It is recommended to ignore the values of those bits. During a "Write Status Register" instruction, the Reserved Bits can be written as "0", but there will not be any effects.

## 7.4 W25N512GV Status Register Memory Protection

	STATU	JS REGI	STER <sup>(1)</sup>		W25N512GV (512M-BIT / 64M-BYTE) MEMORY PROTECTION <sup>(2)</sup>					
тв	BP3	BP2	BP1	BP0	PROTECTED BLOCK(S)	PROTECTED PAGE ADDRESS PA[15:0]	PROTECTED DENSITY	PROTECTED PORTION		
х	0	0	0	0	NONE	NONE	NONE	NONE		
0	0	0	0	1	511	7FC0h - 7FFFh	128KB	Upper 1/512		
0	0	0	1	0	510 & 511	7F80h - 7FFFh	256KB	Upper 1/256		
0	0	0	1	1	508 thru 511	7F00h - 7FFFh	512KB	Upper 1/128		
0	0	1	0	0	504 thru 511	7E00h - 7FFFh	1MB	Upper 1/64		
0	0	1	0	1	496 thru 511	7C00h - 7FFFh	2MB	Upper 1/32		
0	0	1	1	0	480 thru 511	7800h - 7FFFh	4MB	Upper 1/16		
0	0	1	1	1	448 thru 511	7000h - 7FFFh	8MB	Upper 1/8		
0	1	0	0	0	384 thru 511	6000h - 7FFFh	16MB	Upper 1/4		
0	1	0	0	1	256 thru 511	4000h - 7FFFh	32MB	Upper 1/2		
1	0	0	0	1	0	0000h - 003Fh	128KB	Lower 1/512		
1	0	0	1	0	0 & 1	0000h - 007Fh	256KB	Lower 1/256		
1	0	0	1	1	0 thru 3	0000h - 00FFh	512KB	Lower 1/128		
1	0	1	0	0	0 thru 7	0000h - 01FFh	1MB	Lower 1/64		
1	0	1	0	1	0 thru 15	0000h - 03FFh	2MB	Lower 1/32		
1	0	1	1	0	0 thru 31	0000h - 07FFh	4MB	Lower 1/16		
1	0	1	1	1	0 thru 63	0000h - 0FFFh	8MB	Lower 1/8		
1	1	0	0	0	0 thru 127	0000h - 1FFFh	16MB	Lower 1/4		
1	1	0	0	1	0 thru 255	0000h - 3FFFh	32MB	Lower 1/2		
Х	1	0	1	Х	0 thru 511	0000h - 7FFFh	64MB	ALL		
Х	1	1	Х	Х	0 thru 511	0000h - 7FFFh	64MB	ALL		

#### Notes:

1. X = don't care

2. If any Erase or Program command specifies a memory region that contains protected data portion, this command will be ignored.

## 8. INSTRUCTIONS

The Standard/Dual/Quad SPI instruction set of the W25N512GV consists of 31 basic instructions that are fully controlled through the SPI bus (see Instruction Set Table1, 2). Instructions are initiated with the falling edge of Chip Select (/CS). The first byte of data clocked into the DI input provides the instruction code. Data on the DI input is sampled on the rising edge of clock with most significant bit (MSB) first.

winbond

Instructions vary in length from a single byte to several bytes and may be followed by address bytes, data bytes, dummy bytes (don't care), and in some cases, a combination. Instructions are completed with the rising edge of edge /CS. Clock relative timing diagrams for each instruction are included in Figures 5 through 32. All read instructions can be completed after any clocked bit. However, all instructions that Write, Program or Erase must complete on a byte boundary (/CS driven high after a full 8-bits have been clocked) otherwise the instruction will be ignored. This feature further protects the device from inadvertent writes. Additionally, while the device is performing Program or Erase operation, BBM management, Page Data Read or OTP locking operations, BUSY bit will be high, and all instructions except for Read Status Register or Read JEDEC ID will be ignored until the current operation cycle has completed.

### 8.1 Device ID and Instruction Set Tables

## 8.1.1 Manufacturer and Device Identification

MANUFACTURER ID	(MF7 - MF0)
Winbond Serial Flash	EFh
Device ID	(ID15 - ID0)
W25N512GV	AA20h

## 8.1.2 Instruction Set Table 1 (Continuous Read, BUF = 0, xxT Default Power Up Mode)<sup>(11)</sup>

Commands	OpCode	Byte2	Byte3	Byte4	Byte5	Byte6	Byte7	Byte8	Byte9
Device RESET	FFh					•			
JEDEC ID	9Fh	Dummy	<u>EFh</u>	<u>AAh</u>	<u>20h</u>				
Read Status Register	0Fh / 05h	SR Addr	<u> \$7-0</u>	<u> \$7-0</u>	<u> \$7-0</u>	<u> \$7-0</u>	<u> 87-0</u>	<u> \$7-0</u>	<u> 87-0</u>
Write Status Register	1Fh / 01h	SR Addr	S7-0		I	1		1	
Write Enable	06h								
Write Disable	04h								
BB Management (Swap Blocks)	A1h	LBA	LBA	PBA	PBA				
Read BBM LUT	A5h	Dummy	<u>LBA0</u>	<u>LBA0</u>	PBA0	<u>PBA0</u>	<u>LBA1</u>	<u>LBA1</u>	PBA1
Last ECC failure Page Address	A9h	Dummy	<u>PA15-8</u>	<u>PA7-0</u>				•	
Block Erase	D8h	Dummy	PA15-8	PA7-0					
Program Data Load (Reset Buffer)	02h	CA15-8	CA7-0	Data-0	Data-1	Data-2	Data-3	Data-4	Data-5
Random Program Data Load	84h	CA15-8	CA7-0	Data-0	Data-1	Data-2	Data-3	Data-4	Data-5
Quad Program Data Load (Reset Buffer)	32h	CA15-8	CA7-0	Data-0 / 4	Data-1 / 4	Data-2 / 4	Data-3 / 4	Data-4 / 4	Data-5 / 4
Random Quad Program Data Load	34h	CA15-8	CA7-0	Data-0 / 4	Data-1 / 4	Data-2 / 4	Data-3 / 4	Data-4 / 4	Data-5 / 4
Program Execute	10h	Dummy	PA15-8	PA7-0		•		•	
Page Data Read	13h	Dummy	PA15-8	PA7-0					
Read	03h	Dummy	Dummy	Dummy	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>
Fast Read	0Bh	Dummy	Dummy	Dummy	Dummy	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>
Fast Read with 4-Byte Address	0Ch	Dummy	Dummy	Dummy	Dummy	Dummy	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>
Fast Read Dual Output	3Bh	Dummy	Dummy	Dummy	Dummy	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>
Fast Read Dual Output with 4-Byte Address	3Ch	Dummy	Dummy	Dummy	Dummy	Dummy	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>
Fast Read Quad Output	6Bh	Dummy	Dummy	Dummy	Dummy	<u>D7-0 / 4</u>	<u>D7-0 / 4</u>	<u>D7-0 / 4</u>	<u>D7-0/4</u>
Fast Read Quad Output with 4-Byte Address	6Ch	Dummy	Dummy	Dummy	Dummy	Dummy	<u>D7-0 / 4</u>	<u>D7-0 / 4</u>	<u>D7-0/4</u>
Fast Read Dual I/O	BBh	Dummy / 2	Dummy / 2	Dummy / 2	Dummy / 2	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>
Fast Read Dual I/O with 4-Byte Address	BCh	Dummy / 2	Dummy / 2	Dummy / 2	Dummy / 2	Dummy / 2	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>
Fast Read Quad I/O	EBh	Dummy / 4	Dummy / 4	Dummy / 4	Dummy / 4	Dummy / 4	Dummy / 4	<u>D7-0 / 4</u>	<u>D7-0/4</u>
Fast Read Quad I/O with 4-Byte Address	ECh	Dummy / 4	Dummy / 4	Dummy / 4	Dummy / 4	Dummy / 4	Dummy / 4	Dummy / 4	<u>D7-0/4</u>
Deep Power-Down	B9h		•	•		•		•	
Release Power-Down	ABh								
Chip Erase	C7h/60h								
Enable Reset	66h								
Reset Device	99h								

1

8.1.3 Instruction Set Table 2 (Buffer Read, BUF = 1, xxG Default Power Up Mode)<sup>(12)</sup>

Commands	OpCode	Byte2	Byte3	Byte4	Byte5	Byte6	Byte7	Byte8	Byte9
Device RESET	FFh			•		•			
JEDEC ID	9Fh	Dummy	<u>EFh</u>	<u>AAh</u>	<u>20h</u>				
Read Status Register	0Fh / 05h	SR Addr	<u> 87-0</u>	<u> 87-0</u>	<u> 87-0</u>	<u> 87-0</u>	<u> 87-0</u>	<u> 87-0</u>	<u> 87-0</u>
Write Status Register	1Fh / 01h	SR Addr	S7-0		1	1		I	
Write Enable	06h		L	•					
Write Disable	04h								
BB Management (Swap Blocks)	A1h	LBA	LBA	PBA	PBA				
Read BBM LUT	A5h	Dummy	<u>LBA0</u>	<u>LBA0</u>	PBA0	<u>PBA0</u>	<u>LBA1</u>	<u>LBA1</u>	<u>PBA1</u>
Last ECC failure Page Address	A9h	Dummy	<u>PA15-8</u>	<u>PA7-0</u>					
Block Erase	D8h	Dummy	PA15-8	PA7-0					
Program Data Load (Reset Buffer)	02h	CA15-8	CA7-0	Data-0	Data-1	Data-2	Data-3	Data-4	Data-5
Random Program Data Load	84h	CA15-8	CA7-0	Data-0	Data-1	Data-2	Data-3	Data-4	Data-5
Quad Program Data Load (Reset Buffer)	32h	CA15-8	CA7-0	Data-0 / 4	Data-1 / 4	Data-2 / 4	Data-3 / 4	Data-4 / 4	Data-5 / 4
Random Quad Program Data Load	34h	CA15-8	CA7-0	Data-0 / 4	Data-1 / 4	Data-2 / 4	Data-3 / 4	Data-4 / 4	Data-5 / 4
Program Execute	10h	Dummy	PA15-8	PA7-0					
Page Data Read	13h	Dummy	PA15-8	PA7-0					
Read	03h	CA15-8	CA7-0	Dummy	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>
Fast Read	0Bh	CA15-8	CA7-0	Dummy	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>
Fast Read with 4-Byte Address	0Ch	CA15-8	CA7-0	Dummy	Dummy	Dummy	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>
Fast Read Dual Output	3Bh	CA15-8	CA7-0	Dummy	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>
Fast Read Dual Output with 4-Byte Address	3Ch	CA15-8	CA7-0	Dummy	Dummy	Dummy	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>
Fast Read Quad Output	6Bh	CA15-8	CA7-0	Dummy	<u>D7-0 / 4</u>	<u>D7-0 / 4</u>	<u>D7-0 / 4</u>	<u>D7-0 / 4</u>	<u>D7-0/4</u>
Fast Read Quad Output with 4-Byte Address	6Ch	CA15-8	CA7-0	Dummy	Dummy	Dummy	<u>D7-0 / 4</u>	<u>D7-0 / 4</u>	<u>D7-0/4</u>
Fast Read Dual I/O	BBh	CA15-8/2	CA7-0/2	Dummy / 2	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>
Fast Read Dual I/O with 4-Byte Address	BCh	CA15-8/2	CA7-0 / 2	Dummy / 2	Dummy / 2	Dummy / 2	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>
Fast Read Quad I/O	EBh	CA15-8 / 4	CA7-0 / 4	Dummy / 4	Dummy / 4	<u>D7-0 / 4</u>	<u>D7-0 / 4</u>	<u>D7-0 / 4</u>	<u>D7-0/4</u>
Fast Read Quad I/O with 4-Byte Address	ECh	CA15-8 / 4	CA7-0 / 4	Dummy / 4	Dummy / 4	Dummy / 4	Dummy / 4	Dummy / 4	<u>D7-0/4</u>
Deep Power-Down	B9h			1		1			
Release Power-Down	ABh								
Chip Erase	C7h/60h								
Enable Reset	66h								
Reset Device	99h								

8.1.4 Instruction Set Table 3 (Buffer Read, BUF = 1 Fixed, xxR)<sup>(12)</sup>

Commands	OpCode	Byte2	Byte3	Byte4	Byte5	Byte6	Byte7	Byte8	Byte9
Device RESET	FFh								
JEDEC ID	9Fh	Dummy	<u>EFh</u>	<u>AAh</u>	<u>21h</u>				
Read Status Register	0Fh / 05h	SR Addr	<u>\$7-0</u>	<u>\$7-0</u>	<u> 87-0</u>	<u> 87-0</u>	<u> 87-0</u>	<u>\$7-0</u>	<u>\$7-0</u>
Write Status Register	1Fh / 01h	SR Addr	S7-0					•	•
Write Enable	06h			•					
Write Disable	04h								
Block Erase	D8h	Dummy	PA15-8	PA7-0					
Program Data Load (Reset Buffer)	02h	CA15-8	CA7-0	Data-0	Data-1	Data-2	Data-3	Data-4	Data-5
Random Program Data Load	84h	CA15-8	CA7-0	Data-0	Data-1	Data-2	Data-3	Data-4	Data-5
Quad Program Data Load (Reset Buffer)	32h	CA15-8	CA7-0	Data-0 / 4	Data-1 / 4	Data-2 / 4	Data-3 / 4	Data-4 / 4	Data-5 / 4
Random Quad Program Data Load	34h	CA15-8	CA7-0	Data-0 / 4	Data-1 / 4	Data-2 / 4	Data-3 / 4	Data-4 / 4	Data-5 / 4
Program Execute	10h	Dummy	PA15-8	PA7-0					
Page Data Read	13h	Dummy	PA15-8	PA7-0					
Read	03h	CA15-8	CA7-0	Dummy	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>
Fast Read	0Bh	CA15-8	CA7-0	Dummy	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>	<u>D7-0</u>
Fast Read Dual Output	3Bh	CA15-8	CA7-0	Dummy	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>
Fast Read Quad Output	6Bh	CA15-8	CA7-0	Dummy	<u>D7-0/4</u>	<u>D7-0/4</u>	<u>D7-0/4</u>	<u>D7-0 / 4</u>	<u>D7-0/4</u>
Fast Read Dual I/O	BBh	CA15-8 / 2	CA7-0 / 2	Dummy / 2	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>	<u>D7-0/2</u>
Fast Read Quad I/O	EBh	CA15-8 / 4	CA7-0 / 4	Dummy / 4	Dummy / 4	<u>D7-0/4</u>	<u>D7-0/4</u>	<u>D7-0/4</u>	<u>D7-0/4</u>

Notes:

5.

- 1. Output designates data output from the device.
- 2. Column Address (CA) only requires CA[11:0], CA[15:12] are considered as dummy bits.
- Page Address (PA) requires 15 bits. PA[14:6] is the address for 128KB blocks (total 512 blocks), PA[5:0] is the address for 2KB pages (total 64 pages for each block).

winbond

4. Logical and Physical Block Address (LBA & PBA) each consists of 16 bits. LBA[9:0] & PBA[9:0] are effective Block Addresses. LBA[15:14] is used for additional information.

Status Register Addresses:	
Status Register 1 / Protection Register:	Addr = Axh
Status Register 2 / Configuration Register:	Addr = Bxh
Status Register 3 / Status Register:	Addr = Cxh

- Dual SPI Address Input (CA15-8 / 2 and CA7-0 / 2) format: IO0 = x, x, CA10, CA8, CA6, CA4, CA2, CA0 IO1 = x, x, CA11, CA9, CA7, CA5, CA3, CA1
- Dual SPI Data Output (<u>D7-0/2</u>) format: IO0 = D6, D4, D2, D0, ..... IO1 = D7, D5, D3, D1, .....
- 8. Quad SPI Address Input (CA15-8 / 4 and CA7-0 / 4) format:

IO0 =	Х,	CA8,	CA4,	CA0
IO1 =	Х,	CA9,	CA5,	CA1
IO2 =	Х,	CA10,	CA6,	CA2
IO3 =	х,	CA11,	CA7,	CA3

9. Quad SPI Data Input/Output (D7-0/4) format:

IO0 =	D4,	D0,	
IO1 =	D5,	D1,	

- IO2 = D6, D2, .....
- IO3 = D7, D3, .....
- 10. All Quad Program/Read commands are disabled when WP-E bit is set to 1 in the Protection Register.
- 11. For all Read operations in the Continuous Read Mode, once the /CS signal is brought to high to terminate the read operation, the device will still remain busy for tRD3 (BUSY=1), and all the data inside the Data Buffer will be lost and un-reliable to use. A new Page Data Read instruction must be issued to reload the correct page data into the Data Buffer.
- 12. For all Read operations in the Buffer Read Mode, as soon as /CS signal is brought to high to terminate the read operation, the device will be ready to accept new instructions and all the data inside the Data Buffer will remain unchanged from the previous Page Data Read instruction.



## 8.2.1 Device Reset (FFh), Enable Reset (66h) and Reset Device (99h)

Because of the small package and the limitation on the number of pins, the W25N512GV provide a software Reset instruction instead of a dedicated RESET pin. Once the Reset instruction is accepted, any on-going internal operations will be terminated and the device state bits will follow the below table. Once the Reset command is accepted by the device, the device will take approximately tRST to reset, depending on the current operation the device is performing, tRST can be 5us~500us. During this period, no command will be accepted.

Data corruption may happen if there is an on-going internal Erase or Program operation when Reset command sequence is accepted by the device. It is recommended to check the BUSY bit in Status Register before issuing the Reset command.




Figure 5a. Device Reset Instruction




Figure 5b. Enable Reset and Reset Instruction Sequence

	/ /			ÍΠ	60	nd		
Register	Address	Bits	Shipment Default	Power Up after LUT is full	Power Up after OTP area locked	Power Up after SR-1 locked	After Reset (FFh) Command	After Reset (66h+99h) Command or HW Reset
		BP[3:0], TB	1111, 1	1111, 1	1111, 1	xxxx, x (locked)	No Change	1111, 1
Protection Register	Axh	SRP[1:0]	0 0	0 0	0 0	1 1 (locked)	No Change	0 0
register		WP-E	0	0	0	x (locked)	No Change	0
		OTP-L	0	0	1	0	Clear to 0 before OTP set	Clear to 0 before OTP set
	Bxh	OTP-E	0	0	0	0	0	0
		SR1-L	0	0	0	1	Clear to 0 before OTP set	Clear to 0 before OTP set
Configuration		ECC-E	1	1	1	1	No Change	1
Register		BUF(xxG)	1	1	1	1	No Change	1
		BUF(xxT)	0	0	0	0	No Change	0
		BUF(xxR)	1	1	1	1	1	1
		ODS[1:0]	10	1 0	1 0	10	No Change	10
		H-DIS	1	1	1	1	No Change	1
		LUT-F	0	1	0	0	No Change	No Change
		ECC-1	0	0	0	0	0	0
Status	Cxh	ECC-0	0	0	0	0	0	0
Register	Cxn	P-FAIL	0	0	0	0	0	0
		E-FAIL	0	0	0	0	0	0
		WEL	0	0	0	0	0	0
Page 0 F	Reload		Page 0 reload	Page 0 reload	Page 0 reload	Page 0 reload	Fix no reload	Option page reload (default no reload)

Default values of the Status Registers after power up and Device Reset

winbond

## 8.2.2 Read JEDEC ID (9Fh)

The Read JEDEC ID instruction is compatible with the JEDEC standard for SPI compatible serial memories that was adopted in 2003. The instruction is initiated by driving the /CS pin low and shifting the instruction code "9Fh" followed by 8 dummy clocks. The JEDEC assigned Manufacturer ID byte for Winbond (EFh) and two Device ID bytes are then shifted out on the falling edge of CLK with most significant bit (MSB) first as shown in Figure 6. For memory type and capacity values refer to Manufacturer and Device Identification table.




Figure 6. Read JEDEC ID Instruction

## 8.2.3 Read Status Register (0Fh / 05h)

## The Read Status Register instructions allow the 8-bit Status Registers to be read. The instruction is entered by driving /CS low and shifting the instruction code "0Fh or 05h" into the DI pin on the rising edge of CLK followed by an 8-bit Status Register Address. The status register bits are then shifted out on the DO pin at

followed by an 8-bit Status Register Address. The status register bits are then shifted out on the DO pin at the falling edge of CLK with most significant bit (MSB) first as shown in Figure 7. Refer to section 7.1-3 for Status Register descriptions.

The Read Status Register instruction may be used at any time, even while a Program or Erase cycle is in progress. This allows the BUSY status bit to be checked to determine when the cycle is complete and if the device can accept another instruction. The Status Register can be read continuously. The instruction is completed by driving /CS high.




Figure 7. Read Status Register Instruction

## 8.2.4 Write Status Register (1Fh / 01h)

The Write Status Register instruction allows the Status Registers to be written. The writable Status Register bits include: SRP[1:0], TB, BP[3:0] and WP-E bit in Status Register-1; OTP-L, OTP-E, SR1-L, ECC-E and BUF bit in Status Register-2. All other Status Register bit locations are read-only and will not be affected by the Write Status Register instruction.

To write the Status Register bits, the instruction is entered by driving /CS low, sending the instruction code "1Fh or 01h", followed by an 8-bit Status Register Address, and then writing the status register data byte as illustrated in Figure 8.

Refer to section 7.1-3 for Status Register descriptions. After power up, factory default for BP[3:0], TB, ECC-E bits are 1, while other bits are 0.




Figure 8. Write Status Register-1/2/3 Instruction

2.5 Write Enable (06b)

## 8.2.5 Write Enable (06h)

The Write Enable instruction (Figure 9) sets the Write Enable Latch (WEL) bit in the Status Register to a 1. The WEL bit must be set prior to every Page Program, Quad Page Program, Block Erase, Chip Erase and Bad Block Management instruction. The Write Enable instruction is entered by driving /CS low, shifting the instruction code "06h" into the Data Input (DI) pin on the rising edge of CLK, and then driving /CS high.




Figure 9. Write Enable Instruction

#### 8.2.6 Write Disable (04h)

The Write Disable instruction (Figure 10) resets the Write Enable Latch (WEL) bit in the Status Register to a 0. The Write Disable instruction is entered by driving /CS low, shifting the instruction code "04h" into the DI pin and then driving /CS high. Note that the WEL bit is automatically reset after Power-up and upon completion of the Page Program, Quad Page Program, Block Erase, Chip Erase, Reset and Bad Block Management instructions.




Figure 10. Write Disable Instruction

**The set of the set of** 

### 8.2.7 Bad Block Management (A1h)


Due to large NAND memory density size and the technology limitation, NAND memory devices are allowed to be shipped to the end customers with certain amount of "Bad Blocks" found in the factory testing. Up to 2% of the memory blocks can be marked as "Bad Blocks" upon shipment, which is a maximum of 10 blocks for W25N512GV. In order to identify these bad blocks, it is recommended to scan the entire memory array for bad block markers set in the factory. A "Bad Block Marker" is a non-FFh data byte stored at Byte 0 of Page 0 for each bad block. An additional marker is also stored in the first two byte of the 64-Byte spare area.

W25N512GV offers a convenient method to manage the bad blocks typically found in NAND flash memory after extensive use. The "Bad Block Management" command is initiated by shifting the instruction code "A1h" into the DI pin and followed by the 16-bits "Logical Block Address" and 16-bits "Physical Block Address". The logical block address is the address for the "bad" block that will be replaced by the "good" block indicated by the physical block address.

A Write Enable instruction must be executed before the device will accept the Bad Block Management instruction (Status Register bit WEL=1). The Bad Block Management instruction is initiated by driving the /CS pin low and shifting the instruction code "A1h" followed by 16-bits LBA (Bad Block address) and the 16-bits PBA (Good Block address). After /CS is driven high to complete the instruction cycle, the self-timed Bad Block Management instruction will commence for a time duration of tPP (See AC Characteristics). While the Bad Block Management cycle is in progress, the Read Status Register instruction may still be used for checking the status of the BUSY bit. The BUSY bit is a 1 during the Bad Block Management cycle and becomes a 0 when the cycle is finished and the device is ready to accept other instructions again. After the Bad Block Management cycle has finished, the Write Enable Latch (WEL) bit in the Status Register is cleared to 0.

Once a Bad Block Management command is successfully executed, the specified LBA-PBA link will be added to the internal Look Up Table (LUT). Up to 10 links can be established in the non-volatile LUT. If all 10 links have been written, the LUT-F bit in the Status Register will become a 1, and no more LBA-PBA links can be established. Therefore, prior to issuing the Bad Block Management command, the LUT-F bit value can be checked or a "Read BBM Look Up Table" command can be issued to confirm if spare links are still available in the LUT.

To guarantee a continuous read operation on the first 500 blocks, the manufacturer may have used some of the BBM LUT entrees. It is advisable for the user to scan all blocks and keep a table of all manufacturer bad blocks prior to first erase/program operation.



Registering the same address in multiple PBAs is prohibited. It may cause unexpected behavior.

Figure 11. Bad Block Management Instruction

**HEAD** winbond

W25N512GVxxG/T/R

## 8.2.8 Read BBM Look Up Table (A5h)

The internal Look Up Table (LUT) consists of 10 Logical-Physical memory block links (from LBA0/PBA0 to LBA9/PBA9). The "Read BBM Look Up Table" command can be used to check the existing address links stored inside the LUT.

The "Read BBM Look Up Table" command is initiated by shifting the instruction code "A5h" into the DI pin and followed by 8-bit dummy clocks, at the falling edge of the 16<sup>th</sup> clocks, the device will start to output the 16-bit "Logical Block Address" and the 16-bit "Physical Block Address" as illustrated in Figure 12. All block address links will be output sequentially starting from the first link (LBA0 & PBA0) in the LUT. If there are available links that are unused, the output will contain all "00h" data.

The MSB bits LBA[15:14] of each link are used to indicate the status of the link.

LBA[15] (Enable)	LBA[14] (Invalid)	Descriptions				
0	0	This link is available to use.				
1	0	This link is enabled and it is a valid link.				
1	1	This link was enabled, but it is not valid any more.				
0	1	Not applicable.				




Figure 12. Read BBM Look Up Table Instruction

**FEES** winbond **FEEE** 

#### 8.2.9 Last ECC Failure Page Address (A9h)

To better manage the data integrity, W25N512GV implements internal ECC correction for the entire memory array. When the ECC-E bit in the Status/Configuration Register is set to 1 (also power up default), the internal ECC algorithm is enabled for all Program and Read operations. During a "Program Execute" command for a specific page, the ECC algorithm will calculate the ECC information based on the data inside the 2K-Byte data buffer and write the ECC data into the extra 64-Byte ECC area in the same physical memory page.

During the Read operations, ECC information will be used to verify the data read out from the physical memory array and possible corrections can be made to limited amount of data bits that contain errors. The ECC Status Bits (ECC-1 & ECC-0) will also be set indicating the result of ECC calculation.

For the "Continuous Read Mode (BUF=0)" operation, multiple pages of main array data can be read out continuously by issuing a single read command. Upon finishing the read operation, the ECC status bits should be check to verify if there's any ECC correction or un-correctable errors existed in the read out data. If ECC-1 & ECC-0 equal to (1, 0) or (1, 1), the previous read out data contain one or more pages that contain ECC un-correctable errors. The failure page address (or the last page address if it's multiple pages) can be obtained by issuing the "Last ECC failure Page Address" command as illustrated in Figure 13. The 16-bit Page Address that contains un-correctable ECC errors will be presented on the DO pin following the instruction code "A9h" and 8-bit dummy clocks on the DI pin.




Figure 13. Last ECC Failure Page Address Instruction

# **\_\_\_\_** winbond **\_\_\_**

W25N512GVxxG/T/R

#### 8.2.10 128KB Block Erase (D8h)

The 128KB Block Erase instruction sets all memory within a specified block (64-Pages, 128K-Bytes) to the erased state of all 1s (FFh). A Write Enable instruction must be executed before the device will accept the Block Erase Instruction (Status Register bit WEL must equal 1). The instruction is initiated by driving the /CS pin low and shifting the instruction code "D8h" followed by 8-bit dummy clocks and the 16-bit page address. The Block Erase instruction sequence is shown in Figure 14.

The /CS pin must be driven high after the eighth bit of the last byte has been latched. If this is not done the Block Erase instruction will not be executed. After /CS is driven high, the self-timed Block Erase instruction will commence for a time duration of tBE (See AC Characteristics). While the Block Erase cycle is in progress, the Read Status Register instruction may still be accessed for checking the status of the BUSY bit. The BUSY bit is a 1 during the Block Erase cycle and becomes a 0 when the cycle is finished and the device is ready to accept other instructions again. After the Block Erase cycle has finished the Write Enable Latch (WEL) bit in the Status Register is cleared to 0. The Block Erase instruction will not be executed if the addressed block is protected by the Block Protect (TB, BP2, BP1, and BP0) bits.




Figure 14. 128KB Block Erase Instruction

# **FEES winbond**

#### 8.2.11 Load Program Data (02h) / Random Load Program Data (84h)

The Program operation allows from one byte to 2,112 bytes (a page) of data to be programmed at previously erased (FFh) memory locations. A Program operation involves two steps: 1. Load the program data into the Data Buffer. 2. Issue "Program Execute" command to transfer the data from Data Buffer to the specified memory page.

A Write Enable instruction must be executed before the device will accept the Load Program Data Instructions (Status Register bit WEL= 1). The "Load Program Data" or "Random Load Program Data" instruction is initiated by driving the /CS pin low then shifting the instruction code "02h" or "84h" followed by a 16-bit column address (only CA[11:0] is effective) and at least one byte of data into the DI pin. The /CS pin must be held low for the entire length of the instruction while data is being sent to the device. If the number of data bytes sent to the device exceeds the number of data bytes in the Data Buffer, the extra data will be ignored by the device. The Load Program Data instruction sequence is shown in Figure 15.

Both "Load Program Data" and "Random Load Program Data" instructions share the same command sequence. The difference is that "Load Program Data" instruction will reset the unused the data bytes in the Data Buffer to FFh value, while "Random Load Program Data" instruction will only update the data bytes that are specified by the command input sequence, the rest of the Data Buffer will remain unchanged.

If internal ECC algorithm is enabled, all 2,112 bytes of data will be accepted, but the bytes designated for ECC parity bits in the extra 64 bytes section will be overwritten by the ECC calculation. If the ECC-E bit is set to a 0 to disable the internal ECC, the extra 64 bytes section can be used for external ECC purpose or other usage.




Figure 15. Load / Random Load Program Data Instruction





#### 8.2.12 Quad Load Program Data (32h) / Quad Random Load Program Data (34h)

The "Quad Load Program Data" and "Quad Random Load Program Data" instructions are identical to the "Load Program Data" and "Random Load Program Data" in terms of operation sequence and functionality. The only difference is that "Quad Load" instructions will input the data bytes from all four IO pins instead of the single DI pin. This method will significantly shorten the data input time when a large amount of data needs to be loaded into the Data Buffer. The instruction sequence is illustrated in Figure 16.

Both "Quad Load Program Data" and "Quad Random Load Program Data" instructions share the same command sequence. The difference is that "Quad Load Program Data" instruction will reset the unused the data bytes in the Data Buffer to FFh value, while "Quad Random Load Program Data" instruction will only update the data bytes that are specified by the command input sequence, the rest of the Data Buffer will remain unchanged.

/CS 0 7 Mode 3 8 24 25 26 27 Mode 3 23 CLK Mode 0 Mode 0 Column Instruction Addr[15:0] DI 32h / 34h 15 0 0 0 0 4 0 4 4 4  $(IO_0)$ High Impedance DO 5 5 1 5 1 1 5  $(IO_1)$ **High Impedance**  $IO_2$ 2 6 2 6 2 6 6 2 High /Hold 7 3 3 7 3 7 3  $(IO_3)$ Data Data Data 0 2111 1

When WP-E bit in the Status Register is set to a 1, all Quad SPI instructions are disabled.

Figure 16. Quad Load / Quad Random Load Program Data Instruction

#### 8.2.13 Program Execute (10h)

The Program Execute instruction is the second step of the Program operation. After the program data are loaded into the 2,112-Byte Data Buffer (or 2,048 bytes when ECC is enabled), the Program Execute instruction will program the Data Buffer content into the physical memory page that is specified in the instruction. The instruction is initiated by driving the /CS pin low then shifting the instruction code "10h" followed by 8-bit dummy clocks and the 16-bit Page Address into the DI pin as shown in Figure 17.

After /CS is driven high to complete the instruction cycle, the self-timed Program Execute instruction will commence for a time duration of tpp (See AC Characteristics). While the Program Execute cycle is in progress, the Read Status Register instruction may still be used for checking the status of the BUSY bit. The BUSY bit is a 1 during the Program Execute cycle and becomes a 0 when the cycle is finished and the device is ready to accept other instructions again. After the Program Execute cycle has finished, the Write Enable Latch (WEL) bit in the Status Register is cleared to 0. The Program Execute instruction will not be executed if the addressed page is protected by the Block Protect (TB, BP2, BP1, and BP0) bits. Only 4 partial page program times are allowed on every single page.

The pages within the block have to be programmed sequentially from the lower order page address to the higher order page address within the block. Programming pages out of sequence is prohibited.




Figure 17. Program Execute Instruction

8.2.14 Page Data Read (13h)

The Page Data Read instruction will transfer the data of the specified memory page into the 2,112-Byte Data Buffer. The instruction is initiated by driving the /CS pin low then shifting the instruction code "13h" followed by 8-bit dummy clocks and the 16-bit Page Address into the DI pin as shown in Figure 18.

winbond

After /CS is driven high to complete the instruction cycle, the self-timed Read Page Data instruction will commence for a time duration of tRD (See AC Characteristics). While the Read Page Data cycle is in progress, the Read Status Register instruction may still be used for checking the status of the BUSY bit. The BUSY bit is a 1 during the Read Page Data cycle and becomes a 0 when the cycle is finished and the device is ready to accept other instructions again.

After the 2,112 bytes of page data are loaded into the Data Buffer, several Read instructions can be issued to access the Data Buffer and read out the data. Depending on the BUF bit setting in the Status Register, either "Buffer Read Mode" or "Continuous Read Mode" may be used to accomplish the read operations.




Figure 18. Page Data Read Instruction

8.2.15 Read Data (03h)

The Read Data instruction allows one or more data bytes to be sequentially read from the Data Buffer after executing the Read Page Data instruction. The Read Data instruction is initiated by driving the /CS pin low and then shifting the instruction code "03h" followed by the 16-bit Column Address and 8-bit dummy clocks or a 24-bit dummy clocks into the DI pin. After the address is received, the data byte of the addressed Data Buffer location will be shifted out on the DO pin at the falling edge of CLK with most significant bit (MSB) first. The address is automatically incremented to the next higher address after each byte of data is shifted out allowing for a continuous stream of data. The instruction is completed by driving /CS high.

winbond

The Read Data instruction sequence is shown in Figure 19a & 19b. When BUF=1, the device is in the Buffer Read Mode. The data output sequence will start from the Data Buffer location specified by the 16-bit Column Address and continue to the end of the Data Buffer. Once the last byte of data is output, the output pin will become Hi-Z state. When BUF=0, the device is in the Continuous Read Mode, the data output sequence will start from the first byte of the Data Buffer and increment to the next higher address. When the end of the Data Buffer is reached, the data of the first byte of next memory page will be following and continues through the entire memory array. This allows using a single Read instruction to read out the entire memory array and is also compatible to Winbond's SpiFlash NOR flash memory command sequence.




Figure 19a. Read Data Instruction (Buffer Read Mode, BUF=1)




Figure 19b. Read Data Instruction (Continuous Read Mode, BUF=0)

#### 8.2.16 Fast Read (0Bh)

The Fast Read instruction allows one or more data bytes to be sequentially read from the Data Buffer after executing the Read Page Data instruction. The Fast Read instruction is initiated by driving the /CS pin low and then shifting the instruction code "0Bh" followed by the 16-bit Column Address and 8-bit dummy clocks or a 32-bit dummy clocks into the DI pin. After the address is received, the data byte of the addressed Data Buffer location will be shifted out on the DO pin at the falling edge of CLK with most significant bit (MSB) first. The address is automatically incremented to the next higher address after each byte of data is shifted out allowing for a continuous stream of data. The instruction is completed by driving /CS high.

winbond

The Fast Read instruction sequence is shown in Figure 20a & 20b. When BUF=1, the device is in the Buffer Read Mode. The data output sequence will start from the Data Buffer location specified by the 16-bit Column Address and continue to the end of the Data Buffer. Once the last byte of data is output, the output pin will become Hi-Z state. When BUF=0, the device is in the Continuous Read Mode, the data output sequence will start from the first byte of the Data Buffer and increment to the next higher address. When the end of the Data Buffer is reached, the data of the first byte of next memory page will be following and continues through the entire memory array. This allows using a single Read instruction to read out the entire memory array and is also compatible to Winbond's SpiFlash NOR flash memory command sequence.




Figure 20a. Fast Read Instruction (Buffer Read Mode, BUF=1)




Figure 20b. Fast Read Instruction (Continuous Read Mode, BUF=0)

**FEESS** winbond **FEES** 

#### 8.2.17 Fast Read with 4-Byte Address (0Ch)

The Fast Read instruction allows one or more data bytes to be sequentially read from the Data Buffer after executing the Read Page Data instruction. The Fast Read instruction is initiated by driving the /CS pin low and then shifting the instruction code "0Ch" followed by the 16-bit Column Address and 24-bit dummy clocks (when BUF=1) or a 40-bit dummy clocks (when BUF=0) into the DI pin. After the address is received, the data byte of the addressed Data Buffer location will be shifted out on the DO pin at the falling edge of CLK with most significant bit (MSB) first. The address is automatically incremented to the next higher address after each byte of data is shifted out allowing for a continuous stream of data. The instruction is completed by driving /CS high.

The Fast Read instruction sequence is shown in Figure 21a & 21b. When BUF=1, the device is in the Buffer Read Mode. The data output sequence will start from the Data Buffer location specified by the 16-bit Column Address and continue to the end of the Data Buffer. Once the last byte of data is output, the output pin will become Hi-Z state. When BUF=0, the device is in the Continuous Read Mode, the data output sequence will start from the first byte of the Data Buffer and increment to the next higher address. When the end of the Data Buffer is reached, the data of the first byte of next memory page will be following and continues through the entire memory array. This allows using a single Read instruction to read out the entire memory array and is also compatible to Winbond's SpiFlash NOR flash memory command sequence.




Figure 21a. Fast Read with 4-Byte Address Instruction (Buffer Read Mode, BUF=1)




Figure 21b. Fast Read with 4-Byte Address Instruction (Continuous Read Mode, BUF=0)

# **\_\_\_\_** winbond **\_\_\_**

W25N512GVxxG/T/R

#### 8.2.18 Fast Read Dual Output (3Bh)

The Fast Read Dual Output (3Bh) instruction is similar to the standard Fast Read (0Bh) instruction except that data is output on two pins;  $IO_0$  and  $IO_1$ . This allows data to be transferred at twice the rate of standard SPI devices.

The Fast Read Dual Output instruction sequence is shown in Figure 22a & 22b. When BUF=1, the device is in the Buffer Read Mode. The data output sequence will start from the Data Buffer location specified by the 16-bit Column Address and continue to the end of the Data Buffer. Once the last byte of data is output, the output pin will become Hi-Z state. When BUF=0, the device is in the Continuous Read Mode, the data output sequence will start from the first byte of the Data Buffer and increment to the next higher address. When the end of the Data Buffer is reached, the data of the first byte of next memory page will be following and continues through the entire memory array. This allows using a single Read instruction to read out the entire memory array and is also compatible to Winbond's SpiFlash NOR flash memory command sequence.




Figure 22a. Fast Read Dual Output Instruction (Buffer Read Mode, BUF=1)




Figure 22b. Fast Read Dual Output Instruction (Continuous Read Mode, BUF=0)

#### 8.2.19 Fast Read Dual Output with 4-Byte Address (3Ch)

The Fast Read Dual Output (3Ch) instruction is similar to the standard Fast Read (0Bh) instruction except that data is output on two pins;  $IO_0$  and  $IO_1$ . This allows data to be transferred at twice the rate of standard SPI devices.

The Fast Read Dual Output instruction sequence is shown in Figure 23a & 23b. When BUF=1, the device is in the Buffer Read Mode. The data output sequence will start from the Data Buffer location specified by the 16-bit Column Address and continue to the end of the Data Buffer. Once the last byte of data is output, the output pin will become Hi-Z state. When BUF=0, the device is in the Continuous Read Mode, the data output sequence will start from the first byte of the Data Buffer and increment to the next higher address. When the end of the Data Buffer is reached, the data of the first byte of next memory page will be following and continues through the entire memory array. This allows using a single Read instruction to read out the entire memory array and is also compatible to Winbond's SpiFlash NOR flash memory command sequence.




Figure 23a. Fast Read Dual Output with 4-Byte Address Instruction (Buffer Read Mode, BUF=1)




Figure 23b. Fast Read Dual Output with 4-Byte Address Instruction (Continuous Read Mode, BUF=0)

#### 8.2.20 Fast Read Quad Output (6Bh)

The Fast Read Quad Output (6Bh) instruction is similar to the Fast Read Dual Output (3Bh) instruction except that data is output on four pins,  $IO_0$ ,  $IO_1$ ,  $IO_2$ , and  $IO_3$ . The Fast Read Quad Output Instruction allows data to be transferred at four times the rate of standard SPI devices.

The Fast Read Quad Output instruction sequence is shown in Figure 24a & 24b. When BUF=1, the device is in the Buffer Read Mode. The data output sequence will start from the Data Buffer location specified by the 16-bit Column Address and continue to the end of the Data Buffer. Once the last byte of data is output, the output pin will become Hi-Z state. When BUF=0, the device is in the Continuous Read Mode, the data output sequence will start from the first byte of the Data Buffer and increment to the next higher address. When the end of the Data Buffer is reached, the data of the first byte of next memory page will be following and continues through the entire memory array. This allows using a single Read instruction to read out the entire memory array and is also compatible to Winbond's SpiFlash NOR flash memory command sequence.

When WP-E bit in the Status Register is set to a 1, this instruction is disabled.




Figure 24a. Fast Read Quad Output Instruction (Buffer Read Mode, BUF=1)




Figure 24b. Fast Read Quad Output Instruction (Continuous Read Mode, BUF=0)

# W25N512GVxxG/T/R winhand

#### Fast Read Quad Output with 4-Byte Address (6Ch) 8.2.21

The Fast Read Quad Output (6Ch) instruction is similar to the Fast Read Dual Output (3Bh) instruction except that data is output on four pins, IO<sub>0</sub>, IO<sub>1</sub>, IO<sub>2</sub>, and IO<sub>3</sub>. The Fast Read Quad Output Instruction allows data to be transferred at four times the rate of standard SPI devices.

The Fast Read Quad Output instruction sequence is shown in Figure 25a & 25b. When BUF=1, the device is in the Buffer Read Mode. The data output sequence will start from the Data Buffer location specified by the 16-bit Column Address and continue to the end of the Data Buffer. Once the last byte of data is output, the output pin will become Hi-Z state. When BUF=0, the device is in the Continuous Read Mode, the data output sequence will start from the first byte of the Data Buffer and increment to the next higher address. When the end of the Data Buffer is reached, the data of the first byte of next memory page will be following and continues through the entire memory array. This allows using a single Read instruction to read out the entire memory array and is also compatible to Winbond's SpiFlash NOR flash memory command sequence.

When WP-E bit in the Status Register is set to a 1. this instruction is disabled.




Figure 25a. Fast Read Quad Output with 4-Byte Address Instruction (Buffer Read Mode, BUF=1)




Figure 25b. Fast Read Quad Output with 4-Byte Address Instruction (Continuous Read Mode, BUF=0)

#### 8.2.22 Fast Read Dual I/O (BBh)

The Fast Read Dual I/O (BBh) instruction allows for improved random access while maintaining two IO pins,  $IO_0$  and  $IO_1$ . It is similar to the Fast Read Dual Output (3Bh) instruction but with the capability to input the Column Address or the dummy clocks two bits per clock. This reduced instruction overhead may allow for code execution (XIP) directly from the Dual SPI in some applications.

The Fast Read Quad Output instruction sequence is shown in Figure 26a & 26b. When BUF=1, the device is in the Buffer Read Mode. The data output sequence will start from the Data Buffer location specified by the 16-bit Column Address and continue to the end of the Data Buffer. Once the last byte of data is output, the output pin will become Hi-Z state. When BUF=0, the device is in the Continuous Read Mode, the data output sequence will start from the first byte of the Data Buffer and increment to the next higher address. When the end of the Data Buffer is reached, the data of the first byte of next memory page will be following and continues through the entire memory array. This allows using a single Read instruction to read out the entire memory array and is also compatible to Winbond's SpiFlash NOR flash memory command sequence.




Figure 26a. Fast Read Dual I/O Instruction (Buffer Read Mode, BUF=1)




Figure 26b. Fast Read Dual I/O Instruction (Continuous Read Mode, BUF=0)

# **FEESS** Winbond **FEE**

#### 8.2.23 Fast Read Dual I/O with 4-Byte Address (BCh)

The Fast Read Dual I/O (BCh) instruction allows for improved random access while maintaining two IO pins,  $IO_0$  and  $IO_1$ . It is similar to the Fast Read Dual Output (3Bh) instruction but with the capability to input the Column Address or the dummy clocks two bits per clock. This reduced instruction overhead may allow for code execution (XIP) directly from the Dual SPI in some applications.

The Fast Read Quad Output instruction sequence is shown in Figure 27a & 27b. When BUF=1, the device is in the Buffer Read Mode. The data output sequence will start from the Data Buffer location specified by the 16-bit Column Address and continue to the end of the Data Buffer. Once the last byte of data is output, the output pin will become Hi-Z state. When BUF=0, the device is in the Continuous Read Mode, the data output sequence will start from the first byte of the Data Buffer and increment to the next higher address. When the end of the Data Buffer is reached, the data of the first byte of next memory page will be following and continues through the entire memory array. This allows using a single Read instruction to read out the entire memory array and is also compatible to Winbond's SpiFlash NOR flash memory command sequence.




Figure 27a. Fast Read Dual I/O with 4-Byte Address Instruction (Buffer Read Mode, BUF=1)





Figure 27b. Fast Read Dual I/O with 4-Byte Address Instruction (Continuous Read Mode, BUF=0)

#### 8.2.24 Fast Read Quad I/O (EBh)

The Fast Read Quad I/O (EBh) instruction is similar to the Fast Read Dual I/O (BBh) instruction except that address and data bits are input and output through four pins  $IO_0$ ,  $IO_1$ ,  $IO_2$  and  $IO_3$  prior to the data output. The Quad I/O dramatically reduces instruction overhead allowing faster random access for code execution (XIP) directly from the Quad SPI.

The Fast Read Quad Output instruction sequence is shown in Figure 28a & 28b. When BUF=1, the device is in the Buffer Read Mode. The data output sequence will start from the Data Buffer location specified by the 16-bit Column Address and continue to the end of the Data Buffer. Once the last byte of data is output, the output pin will become Hi-Z state. When BUF=0, the device is in the Continuous Read Mode, the data output sequence will start from the first byte of the Data Buffer and increment to the next higher address. When the end of the Data Buffer is reached, the data of the first byte of next memory page will be following and continues through the entire memory array. This allows using a single Read instruction to read out the entire memory array and is also compatible to Winbond's SpiFlash NOR flash memory command sequence.



When WP-E bit in the Status Register is set to a 1, this instruction is disabled.

Figure 28a. Fast Read Quad I/O Instruction (Buffer Read Mode, BUF=1)





Figure 28b. Fast Read Quad I/O Instruction (Continuous Read Mode, BUF=0)

# **FEES winbond**

#### 8.2.25 Fast Read Quad I/O with 4-Byte Address (ECh)

The Fast Read Quad I/O (ECh) instruction is similar to the Fast Read Dual I/O (BBh) instruction except that address and data bits are input and output through four pins  $IO_0$ ,  $IO_1$ ,  $IO_2$  and  $IO_3$  prior to the data output. The Quad I/O dramatically reduces instruction overhead allowing faster random access for code execution (XIP) directly from the Quad SPI.

The Fast Read Quad Output instruction sequence is shown in Figure 29a & 29b. When BUF=1, the device is in the Buffer Read Mode. The data output sequence will start from the Data Buffer location specified by the 16-bit Column Address and continue to the end of the Data Buffer. Once the last byte of data is output, the output pin will become Hi-Z state. When BUF=0, the device is in the Continuous Read Mode, the data output sequence will start from the first byte of the Data Buffer and increment to the next higher address. When the end of the Data Buffer is reached, the data of the first byte of next memory page will be following and continues through the entire memory array. This allows using a single Read instruction to read out the entire memory array and is also compatible to Winbond's SpiFlash NOR flash memory command sequence.



When WP-E bit in the Status Register is set to a 1, this instruction is disabled.

Figure 29a. Fast Read Quad I/O with 4-Byte Address Instruction (Buffer Read Mode, BUF=1)




Figure 29b. Fast Read Quad I/O with 4-Byte Address Instruction (Continuous Read Mode, BUF=0)

# **Man Winbond**

#### 8.2.26 Accessing Unique ID / Parameter / OTP Pages (OTP-E=1)

In addition to the main memory array, the W25N512GV is also equipped with one Unique ID Page, one Parameter Page, and ten OTP Pages.

Page Address	Page Name	Descriptions	Data Length
00h	Unique ID Page	Factory programmed, Read Only	32-Byte x 16
01h	Parameter Page	Factory programmed, Read Only	256-Byte x 3
02h	OTP Page [0]	Program Only, OTP lockable	2,112-Byte
	OTP Pages [1:8]	Program Only, OTP lockable	2,112-Byte
0Bh	OTP Page [9]	Program Only, OTP lockable	2,112-Byte

To access these additional data pages, the OTP-E bit in Status Register-2 must be set to "1" first. Then, Read operations can be performed on Unique ID and Parameter Pages, Read and Program operations can be performed on the OTP pages if it's not already locked. To return to the main memory array operation, OTP-E bit needs to be to set to 0.

#### **Read Operations**

A "Page Data Read" command must be issued followed by a specific page address shown in the table above to load the page data into the main Data Buffer. After the device finishes the data loading (BUSY=0), all Read commands may be used to read the Data Buffer starting from any specified Column Address. Please note all Read commands must now follow the "Buffer Read Mode" command structure (CA[15:0], number of dummy clocks) regardless the previous BUF bit setting. ECC can also be enabled for the OTP page read operations to ensure the data integrity.

#### Program and OTP Lock Operations

OTP pages provide the additional space (2K-Byte x 10) to store important data or security information that can be locked to prevent further modification in the field. These OTP pages are in an erased state set in the factory, and can only be programmed (change data from "1" to "0") until being locked by OTP-L bit in the Configuration/Status Register-2. OTP-E must be first set to "1" to enable the access to these OTP pages, then the program data must be loaded into the main Data Buffer using any "Program Data Load" commands. The "Program Execute" command followed by a specific OTP Page Address is used to initiate the data transfer from the Data Buffer to the OTP page. When ECC is enabled, ECC calculation will be performed during "Program Execute", and the ECC information will be stored into the 64-Byte spare area.

Once the OTP pages are correctly programmed, OTP-L bit can be used to permanently lock these pages so that no further modification is possible. While still in the "OTP Access Mode" (OTP-E=1), user needs to set OTP-L bit in the Configuration/Status Register-2 to "1", and issue a "Program Execute" command(Page address is "don't care"). After the device finishes the OTP lock setting (BUSY=0), the user can set OTP-E to "0" to return to the main memory array operation.

#### SR1-L OTP Lock Operation

The Protection/Status Register-1 contains protection bits that can be set to protect either a portion or the entire memory array from being Programmed/Erased or set the device to either Software Write Protection (WP-E=0) or Hardware Write Protection (WP-E=1). Once the BP[3:0], TB, WP-E bits are set correctly, SRP1 and SRP0 should also be set to "1"s as well to allow SR1-L bit being set to "1" to permanently lock the protection settings in the Status Register-1 (SR1). Similar to the OTP-L setting procedure above, in order to set SR1-L lock bit, the device must enter the "OTP Access Mode" (OTP-E=1) first, and SR1-L bit should be set to "1" prior to the "Program Execute" command(Page address is "don't care"). Once SR1-L is set to "1" (BUSY=0), the user can set OTP-E to "0" to return to the main memory array operation.

# 8.2.27 Parameter Page Data Definitions

The Parameter Page contains 3 identical copies of the 256-Byte Parameter Data. The table below lists all the key data byte locations. All other unspecified byte locations have 00h data as default.

Byte Number	Descriptions	Values
0~3	Parameter page signature	4Fh, 4Eh, 46h, 49h
4~5	Revision number	00h, 00h
6~7	Feature supported	00h, 00h
8~9	Optional command supported	02h, 00h
10~31	Reserved	All 00h
32~43	Device manufacturer	57h, 49h, 4Eh, 42h, 4Fh, 4Eh, 44h, 20h, 20h, 20h, 20h, 20h
44~63	Device model	57h, 32h, 35h, 4Eh, 35h, 31h, 32h, 47h, 56h, 20h, 20h, 20h, 20h, 20h, 20h, 20h, 20
64	JEDEC manufacturer ID	EFh
65~66	Date code	00h, 00h
67~79	Reserved	All 00h
80~83	Number of data bytes per page	00h, 08h, 00h, 00h
84~85	Number of spare bytes per page	40h, 00h
86~91	Reserved	All 00h
92~95	Number of pages per block	40h, 00h, 00h, 00h
96~99	Number of blocks per logical unit	00h, 02h, 00h, 00h
100	Number of logical units	01h
101	Number of address bytes	00h
102	Number of bits per cell	01h
103~104	Bad blocks maximum per unit	0Ah, 00h
105~106	Block endurance	01h, 05h
107	Guaranteed valid blocks at beginning of target	01h
108~109	Block endurance for guaranteed valid blocks	00h, 00h
110	Number of programs per page	04h
111	Reserved	00h
112	Number of ECC bits	00h
113	Number of plane address bits	00h
114	Multi-plane operation attributes	00h
115~127	Reserved	All 00h
128	I/O pin capacitance, maximum	08h
129~132	Reserved	All 00h
133~134	Maximum page program time (us)	BCh, 02h
135~136	Maximum block erase time (us)	10h, 27h
137~138	Maximum page read time (us)	32h, 00h
139~163	Reserved	All 00h
164~165	Vendor specific revision number	00h, 00h
166~253	Vendor specific	All 00h
254~255	Integrity CRC	90h, 37h
256~511	Value of bytes 0~255	
512~767	Value of bytes 0~255	
768~2111	Reserved	

#### 8.2.28 Deep Power-Down (B9h)

Although the standby current during normal operation is relatively low, standby current can be further reduced with the Deep Power-Down instruction. The lower power consumption makes the Power-Down instruction especially useful for battery powered applications (See ICC1 and ICC2 in AC Characteristics). The instruction is initiated by driving the /CS pin low and shifting the instruction code "B9h" as shown in Figure 30.

winbond

The /CS pin must be driven high after the eighth bit has been latched. If this is not done the Power-down instruction will not be executed. After /CS is driven high, the power-down state will entered within the time duration of tDP (See AC Characteristics). While in the power-down state only the Release Power-down / Device ID (ABh) instruction, which restores the device to normal operation, will be recognized. All other instructions are ignored. This includes the Read Status Register instruction, which is always available during normal operation. Ignoring all but one instruction makes the Power Down state a useful condition for securing maximum write protection. The device always powers-up in the normal operation with the standby current of ICC1.




Figure 30. Deep Power-Down Instruction



#### 8.2.29 Release Power-Down (ABh)

The Release from Power-Down instruction is used to release the device from the power-down state.

To release the device from the power-down state, the instruction is issued by driving the /CS pin low, shifting the instruction code "ABh" and driving /CS high as shown in Figure 31. Release from power-down will take the time duration of tRES (See AC Characteristics) before the device will resume normal operation and other instructions are accepted. The /CS pin must remain high during the tRES time duration.




Figure 31. Release Power-down Instruction

#### 8.2.30 Chip Erase (C7h / 60h)

The Chip Erase instruction sets all memory within the device to the erased state of all 1s (FFh). A Write Enable instruction must be executed before the device will accept the Chip Erase Instruction (Status Register bit WEL must equal 1). The instruction is initiated by driving the /CS pin low and shifting the instruction code "C7h" or "60h". The Chip Erase instruction sequence is shown in Figure 32.

The /CS pin must be driven high after the eighth bit has been latched. If this is not done the Chip Erase instruction will not be executed. After /CS is driven high, the self-timed Chip Erase instruction will commence for a time duration of tCE (See AC Characteristics). While the Chip Erase cycle is in progress, the Read Status Register instruction may still be accessed to check the status of the BUSY bit. The BUSY bit is a 1 during the Chip Erase cycle and becomes a 0 when finished and the device is ready to accept other instructions again. After the Chip Erase cycle has finished the Write Enable Latch (WEL) bit in the Status Register is cleared to 0. The Chip Erase instruction will not be executed if any memory region is protected by the Block Protect (TB, BP3, BP2, BP1, and BP0) bits.




Figure 32. Chip Erase Instruction



#### 9.1 Absolute Maximum Ratings<sup>(1)</sup>

PARAMETERS	SYMBOL	CONDITIONS	RANGE	UNIT
Supply Voltage	VCC		-0.6 to +4.6	V
Voltage Applied to Any Pin	Vio	Relative to Ground	-0.6 to +4.6	V
Transient Voltage on any Pin	VIOT	<20nS Transient Relative to Ground	-2.0 to VCC+2.0	V
Storage Temperature	TSTG		–65 to +150	°C
Lead Temperature	TLEAD		See Note (2)	°C
Electrostatic Discharge Voltage	Vesd	Human Body Model <sup>(3)</sup>	-2000 to +2000	V

#### Notes:

1. This device has been designed and tested for the specified operation ranges. Proper operation outside of these levels is not guaranteed. Exposure to absolute maximum ratings may affect device reliability. Exposure beyond absolute maximum ratings may cause permanent damage.

2. Compliant with JEDEC Standard J-STD-20C for small body Sn-Pb or Pb-free (Green) assembly and the European directive on restrictions on hazardous substances (RoHS) 2002/95/EU.

3. JEDEC Standard JESD22-A114A (C1=100pF, R1=1500 ohms, R2=500 ohms).

#### 9.2 Operating Ranges

PARAMETER	SYMBOL	CONDITIONS	SP	EC	UNIT
PARAMETER	STNIDUL	CONDITIONS	MIN	MAX	UNIT
Supply Voltage	VCC		2.7	3.6	V
Ambient Temperature, Operating	ТА	Industrial Grade Industrial Plus Grade	-40	+85 +105	°C

winbond

#### 9.3 Power-up Power-down Timing Requirements

PARAMETER	SYMBOL	SP	UNIT		
FARAMETER	STWBOL	MIN	MAX	UNIT	
VCC (min) to /CS low	tVSL <sup>(1)</sup>	200		μs	
Time Delay Before Write Instruction	tPUW <sup>(1)</sup>	1		ms	
Minimum duration for ensuring initialization will occur	tPWD <sup>(1)</sup>	1		ms	
VCC voltage for ensuring initialization will occur	VPWD <sup>(1)</sup>		0.7	V	

#### Notes:

1. These parameters are characterized only.




Figure 33a. Power-up Power-down Timing and Voltage Levels




Figure 33b. Power-up, Power-Down Requirement

winbond

DADAMETER				SPEC		
PARAMETER	SYMBOL	CONDITIONS	MIN	ТҮР	MAX	UNIT
Input Capacitance	CIN <sup>(1)</sup>	$VIN = 0V^{(1)}$			6	pF
Output Capacitance	Cout <sup>(1)</sup>	$VOUT = 0V^{(1)}$			8	pF
Input Leakage	ILI				<u>+2</u>	μA
I/O Leakage	ILO				±2	μA
Standby Current	ICC1	/CS = VCC, VIN = GND or VCC(85°C)		10	50	
Standby Current		/CS = VCC, VIN = GND or VCC(105°C)		10	100	μΑ
	1000	CS = VCC, VIN = GND or VCC(85°C)		4	10	
Deep Power-Down Current	ICC2	/CS = VCC, VIN = GND or VCC(105°C)		1	20	μA
Read Current	ICC3	C = 0.1 VCC / 0.9 VCC DO = Open		25	35	mA
Current Page Program	ICC4	/CS = VCC		25	35	mA
Current Block/Chip Erase	ICC5	/CS = VCC		25	35	mA
Input Low Voltage	VIL		- 0.5		VCC x 0.3	V
Input High Voltage	Vih		VCC x 0.7		VCC + 0.4	V
Output Low Voltage	Vol	IOL = 2.1mA			0.4	V
Output High Voltage	Voн	ІОН = -400μА	2.4			V

#### 9.4 DC Electrical Characteristics

#### Notes:

The typical (TYP) value is tested on sample basis and specified through design and characterization data. TA = 25° C, VCC = 3.0V.

# 9.5 AC Measurement Conditions

PARAMETER	SYMBOL	SF	UNIT	
FARAMETER	STMBOL	MIN	MAX	UNIT
Load Capacitance	CL		30	pF
Input Rise and Fall Times	Tr, Tf		5	ns
Input Pulse Voltages	Vin	0.1 VCC to 0.9 VCC		V
Input Timing Reference Voltages	IN	0.3 VCC to 0.7 VCC		V
Output Timing Reference Voltages	Out	0.5	V	




Figure 34. AC Measurement I/O Waveform

# 9.6 AC Electrical Characteristics<sup>(3)</sup>

DESCRIPTION	SYMBOL	ALT		UNIT		
	STWIDOL		MIN	TYP	MAX	
Clock frequency for all instructions except Continuous Read (85°C)	F <sub>R</sub>	f <sub>C1</sub>	D.C.		166	MHz
Clock frequency for all instructions except Continuous Read (105°C)	F <sub>R</sub>	fc1	D.C.		133	MHz
Clock frequency for Continuous Read	F <sub>R</sub>	fc2	D.C.		104	MHz
Clock High, Low Time for all instructions	tCLH, tCLL <sup>(1)</sup>		45%PC			ns
Clock Rise Time peak to peak	tCLCH <sup>(2)</sup>		0.1			V/ns
Clock Fall Time peak to peak	tCHCL <sup>(2)</sup>		0.1			V/ns
/CS Active Setup Time relative to CLK	<b>t</b> SLCH	tCSS	5			ns
/CS Not Active Hold Time relative to CLK	tCHSL		5			ns
Data In Setup Time	<b>t</b> DVCH	tDSU	2			ns
Data In Hold Time	<b>tCHDX</b>	tDH	3			ns
/CS Active Hold Time relative to CLK	tCHSH		3			ns
/CS Not Active Setup Time relative to CLK	tshch		3			ns
/CS Deselect Time (for Array Read $\rightarrow$ Array Read)	tSHSL1	tCSH	10			ns
/CS Deselect Time (for Erase, Program or Read Status Registers → Read Status Registers)	tSHSL2	tcsн	50			ns
Output Disable Time	tSHQZ <sup>(2)</sup>	tDIS			7	ns
Clock Low to Output Valid	tCLQV	t∨			6	ns
Output Hold Time	tCLQX	tho	2			ns
/HOLD Active Setup Time relative to CLK	tHLCH		5			ns
/HOLD Active Hold Time relative to CLK	tСННН		5			ns

Continued - next page

# AC Electrical Characteristics (cont'd)

DECODIDITION	0/4/201			SPE	С	
DESCRIPTION	SYMBOL	ALT	MIN	ТҮР	MAX	UNIT
/HOLD Not Active Setup Time relative to CLK	tннсн		5			ns
/HOLD Not Active Hold Time relative to CLK	tCHHL		5			ns
/HOLD to Output Low-Z	thhqx <sup>(2)</sup>	tLZ			7	ns
/HOLD to Output High-Z	tHLQZ <sup>(2)</sup>	tHZ			12	ns
Write Protect Setup Time Before /CS Low	tWHSL		20			ns
Write Protect Hold Time After /CS High	tSHWL		100			ns
Status Register Write Time	tw				50	ns
/CS High to Deep Power-Down Mode	tDP <sup>(2)</sup>				3	μs
/CS High to Standby Mode (Release DPD)	tres <sup>(2)</sup>				3	μs
/CS High to next Instruction after Reset during Page Data Read / Program Execute / Block Erase / Chip Erase	tRST <sup>(2)</sup>				5/10/500	μs
/CS High to next instruction after Reset with page 0 data load option	tRST2				100	us
Read Page Data Time (ECC disabled)	tRD1				25	μs
Read Page Data Time (ECC enabled)	tRD2				60	μs
Continuous Read Stop to Device Ready Time	tRD3				7	μs
Page Program, OTP Lock, BBM Management Time	tPP			250	700	us
Block Erase Time	tBE			2	10	ms
Chip Erase Time	tCE			1	5	s
Number of partial page programs	NoP				4	times

Notes:


1. Clock high + Clock low must be less than or equal to PC. PC=1/fC (MAX).

2. Value guaranteed by design and/or characterization, not 100% tested in production.

3. The typical (TYP) value is tested on sample basis and specified through design and characterization data. TA=25°C, VCC=3.0V.


4. AC electrical characteristics is based on default setting of ODS.

#### 9.7 Serial Output Timing




winbond


#### 9.8 Serial Input Timing



#### 9.9 /HOLD Timing







# 10. INVALID BLOCK MANAGEMENT

#### 10.1 Invalid blocks

The W25N512GV may have initial invalid blocks when it ships from factory. Also, additional invalid blocks may develop during the use of the device. Nvb represents the minimum number of valid blocks in the total number of available blocks (See the below table). An invalid block is defined as blocks that contain one or more bad bits. Block 0, block address 00h is guaranteed to be a valid block at the time of shipment.

Parameter	Symbol	Min	Max	Unit
Valid block number	Nvb	502	512	blocks

Valid Block Number

#### 10.2 Initial invalid blocks

Initial invalid blocks are defined as blocks that contain one or more invalid bits when shipped from factory.

Although the device contains initial invalid blocks, a valid block of the device is of the same quality and reliability as all valid blocks in the device with reference to AC and DC specifications. The W25N512GV has internal circuits to isolate each block from other blocks and therefore, the invalid blocks will not affect the performance of the entire device.

Before the device is shipped from the factory, it will be erased and invalid blocks are permanently marked. The mark information cannot be erased. All initial invalid blocks are marked with non-FFh at the 1st byte of main array and the 1st two bytes of spare area on the 1st page. It should be checked for invalid blocks by reading the marked locations, and create a table of initial invalid blocks as following flow chart.




Figure 35. Flow chart of create initial invalid block table



#### 10.3 Error in Operation

Additional invalid blocks may develop in the device during its life cycle. Following the procedures herein is required to guarantee reliable data in the device.

After each program and erase operation, check the P-FAIL and E-FAIL bit to determine if the operation failed. In case of failure, a block replacement should be done with a bad-block management algorithm. The system has to use a minimum 1-bit ECC per 528 bytes of data to ensure data recovery.

Operation	Detection and recommended procedure
Erase	Status read after erase $\rightarrow$ Block Replacement
Program	Status read after program $\rightarrow$ Block Replacement
Read	Verify ECC $\rightarrow$ ECC correction




Figure 10-1 Bad Block Replacement

#### Notes:


- 1. An error happens in the nth page of block A during program or erase operation.
- 2. Copy the data in block A to the same location of block B which is valid block.
- 3. Copy the nth page data of block A in the buffer memory to the nth page of block B.
- 4. Creating or updating bad block table for preventing further program or erase to block A.

#### **10.4 Addressing in Program Operation**

The pages within the block have to be programmed sequentially from LSB (least significant bit) page to the MSB (most significant bit) within the block. The LSB is defined as the start page to program, does not need to be page 0 in the block. Random page programming is prohibited.




#### 11.1 8-Pad WSON 6x5-mm (Package Code P)



#### Note:

The metal pad area on the bottom center of the package is not connected to any internal electrical signals. It can be left floating or connected to the device ground (GND pin). Avoid placement of exposed PCB vias under the pad.







Symbol	Millimeters Inches					
Symbol	Min	Nom	Max	Min	Nom	Max
А	0.70	0.75	0.80	0.028	0.030	0.031
A1	0.00	0.02	0.05	0.000	0.001	0.002
b	0.35	0.40	0.48	0.014	0.016	0.019
С		0.20 REF			0.008 REF	
D	7.90	8.00	8.10	0.311	0.315	0.319
D2	3.35	3.40	3.45	0.132	0.134	0.136
E	5.90	6.00	6.10	0.232	0.236	0.240
E2	4.25	4.30	4.35	0.167	0.169	0.171
е		1.27			0.050	
L	0.45	0.50	0.55	0.018	0.020	0.022
У	0.00		0.050	0.000		0.002

Note:

The metal pad area on the bottom center of the package is not connected to any internal electrical signals. It can be left floating or connected to the device ground (GND pin). Avoid placement of exposed PCB vias under the pad.



11.4 24-Ball TFBGA 8x6-mm (Package Code B, 5x5-1 Ball Array)



## W25N512GVxxG/T/R winbond **12. ORDERING INFORMATION** W<sup>(1)</sup> 25N 512G V Х Х **Company Prefix** W = Winbond **Product Family** 25N = Serial SLC NAND Memory Product Number / Density 512G = 512M-bit Supply Voltage V = 2.7V to 3.6V Package Type P = WSON8 6x5-mm E = 8-pad WSON 8x6mm F = 16-pin SOIC 300-mil B = 24-ball TFBGA 8x6-mm (5x5 ball array) **Temperature Range** I = Industrial Grade (-40°C to +85°C) J = Industrial Plus Grade (-40°C to +105°C) Special Options<sup>(2)</sup>

- $\label{eq:G} G = Green\ Package\ (Lead-free,\ RoHS\ Compliant,\ Halogen-free\ (TBBA),\ Antimony-Oxide-free\ Sb_2O_3) \\ and\ BUF=1\ is\ the\ default\ value\ after\ power\ up$
- $\label{eq:transform} \begin{array}{l} T = Green\ Package\ (Lead-free,\ RoHS\ Compliant,\ Halogen-free\ (TBBA),\ Antimony-Oxide-free\ Sb_2O_3) \\ and\ BUF=0\ is\ the\ default\ value\ after\ power\ up \end{array}$
- $\label{eq:R} \mbox{R} = \mbox{Green Package (Lead-free, RoHS Compliant, Halogen-free (TBBA), Antimony-Oxide-free Sb_2O_3)} \\ \mbox{and BUF=1 is the fixed value. BUF bit can't be written to 0.}$

Notes:

- 1. The "W" prefix is not included on the part marking.
- 2. Standard bulk shipments are in tray for WSON and TFBGA packages. For other packing options, please specify when placing orders.



#### 12.1 Valid Part Numbers and Top Side Marking

The following table provides the valid part numbers for the W25N512GV SpiFlash Memory. Please contact Winbond for specific availability by density and package type. Winbond SpiFlash memories use a 12-digit Product Number for ordering. However, due to limited space, the Top Side Marking on all packages uses an abbreviated 11-digit number.

PACKAGE TYPE	DENSITY	PRODUCT NUMBER	TOP SIDE MARKING
<b>P</b> WSON-8 6x5mm	512M-bit	W25N512GVPIG	25N512GVPIG
		W25N512GVPIT	25N512GVPIT
		W25N512GVPIR	25N512GVPIR
<b>E</b> WSON-8 8x6mm	512M-bit	W25N512GVEIG	25N512GVEIG
		W25N512GVEIT	25N512GVEIT
		W25N512GVEIR	25N512GVEIR
F SOIC-16 300mil	512M-bit	W25N512GVFIG	25N512GVFIG
		W25N512GVFIT	25N512GVFIT
		W25N512GVFIR	25N512GVFIR
В	В	W25N512GVBIG	25N512GVBIG
TFBGA-24 8x6mm	512M-bit	W25N512GVBIT	25N512GVBIT
(5x5-1 Ball Array)		W25N512GVBIR	25N512GVBIR

#### Part Numbers for Industrial Grade Temperature:

#### Part Numbers for Industrial Plus Grade Temperature:

PACKAGE TYPE	DENSITY	PRODUCT NUMBER	TOP SIDE MARKING
Р		W25N512GVPJG	25N512GVPJG
WSON-8 6x5mm	512M-bit	W25N512GVPJT	25N512GVPJT
		W25N512GVPJR	25N512GVPJR
Е		W25N512GVEJG	25N512GVEJG
⊂ WSON-8 8x6mm	512M-bit	W25N512GVEJT	25N512GVEJT
		W25N512GVEJR	25N512GVEJR
F		W25N512GVFJG	25N512GVFJG
SOIC-16 300mil	512M-bit	W25N512GVFJT	25N512GVFJT
3010-10 3001111		W25N512GVFJR	25N512GVFJR
В		W25N512GVBJG	25N512GVBJG
TFBGA-24 8x6mm	512M-bit	W25N512GVBJT	25N512GVBJT
(5x5-1 Ball Array)		W25N512GVBJR	25N512GVBJR

Note:

W25N512GVxxG: BUF=1 (Buffer Read Mode) is the default value after power up. BUF bit can be written to 0. W25N512GVxxT: BUF=0 (Continuous Read Mode) is the default value after power up. BUF bit can be written to 1. W25N512GVxxR: BUF=1 (Buffer Read Mode) is the fixed value. BUF bit can't be written to 0.

# 13. REVISION HISTORY

VERSION	DATE	PAGE	DESCRIPTION	
A	11/01/2016		New Create Preliminary	
A1	01/12/2017	6,7,64,68,69	Added 6x5-mm WSON Package.	
A2	03/28/2017	25 58	Combined Device Reset (FFh) with Enable Reset(66h) & Reset Device(99h) description. Modified Power-up Timing and Voltage Levels	
A3	07/13/2017	9, 36, 44, 45, 48~51	Updated Hold Pin description and Quad mode waveforms	
A4	12/11/2017	16, 18 27	Updated Configuration Register / Status Register-2. Modified Device Reset (FFh) and Enable Reset(66h) & Reset Device(99h) description and table.	
A5	02/20/2018	13, 20, 31, 32 38 65 59	Updated about Bad Block Management Added description for page program sequence Added Invalid Block Management Updated tVSL spec	
В	06/11/2018	All	Removed Preliminary Designator	
С	02/13/2019	27 6~9, 69~72 60 64 63	Updated Reset Table Removed 6x4 ball TFBGA-24 and added SOIC16 300mil Package Updated tVSL and tPUW Added tRD3 specification Updated tCLQV 7ns to 6ns	
D	08/27/2019	21 6, 12, 18, 26, 29, 60, 62, 64, 72, 73	Revised ECC Status description table. Added Industrial Plus Grade and BUF=1(R suffix) fixed Part numbers	
E	11/16/2020	6 58 62, 65 69 67 68 68 68 72	Updated Features for Cycling and Data Retention. Updated Integrity CRC. Updated Notes. Added Note. Updated the description for the Initial Invalid Block mark Added section for "Error in Operation" Added section for "Addressing in Program Operation" Updated the 5x5 ball BGA package information	
F	04/26/2021	6 12 14 18 20 21 21 21 34 56 61 63 65 67	Updated description of Unique ID and Parameter Page Updated Figure 3 Updated explanation about power-up and power-down sequence Added ECC protected area and constraint when ECC-E=1 Added a Page Data Read command as ECC status bit clear timing Updated Note 1 Updated P-FAIL & E-FAIL bits description Added command sequence explanation sentence for Bad Block Management Updated Byte Number of Reserved Updated Power up and down diagram and specifications Updated Figure 34 Added Note 4 Updated the description for the Initial Invalid Block mark	



#### Trademarks

*Winbond* and *SpiFlash* are trademarks of *Winbond Electronics Corporation*. All other marks are the property of their respective owner.

#### **Important Notice**

*Winbond* products are not designed, intended, authorized or warranted for use as components in systems or equipment intended for surgical implantation, atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, or for other applications intended to support or sustain life. Furthermore, *Winbond* products are not intended for applications wherein failure of *Winbond* products could result or lead to a situation wherein personal injury, death or severe property or environmental damage could occur. *Winbond* customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify *Winbond* for any damages resulting from such improper use or sales.

Information in this document is provided solely in connection with Winbond products. Winbond reserves the right to make changes, corrections, modifications or improvements to this document and the products and services described herein at any time, without notice.

Please note that all data and specifications are subject to change without notice. All the trademarks of products and companies mentioned in this datasheet belong to their respective owners.