


# JF2 SERIES



MODULAR JACK CONNECTORS: 2 PORT RJ45, VERTICAL PCB MOUNT,  
NON-SHIELDED WITH PANEL STOPS

## Features:

- Top performance for high speed networking, voice and data applications
- Meet FCC PART 68, Subpart F requirements
- Advanced EMI/RFI protection with grounding options (PCB or panel)
- Applications: Telecommunications, Broadcast, Data Products
- RoHS Compliant



## Specifications:


Insulator Material	PBT or Nylon
Contact Material	Phosphor Bronze
Contact Plating	Gold Plating on contact area and Tin Plating on tails with Nickel underplating all over
Current Rating	1.5 amps @25°C
Voltage Rating	125 V AC
Contact Resistance	20 milliohms maximum
Dielectric Withstanding Voltage	1000 V AC
Insulation Resistance	500 megaohms minimum
Durability	750 cycles minimum
Operating Temperature	-40°C to +85°C
Wave Soldering Process	260°C ± 5°C, 5~10 Seconds

## Ordering Code:

EXAMPLE PART NUMBER: **JF2028821P00033**

SERIES: RJ MODULAR JACK

HOUSING TYPE: F2-



NO. OF PORTS: 02 - 2 PORT

NO. OF CONTACTS PER PORT: 88 - 8P8C

CONTACT PLATING: 2 - GOLD FLASH  
3 - 15 MICROINCHES OF GOLD  
6 - 30 MICROINCHES OF GOLD  
9 - 50 MICROINCHES OF GOLD

CONTACT TAIL TYPE: 1 - VERTICAL PCB

HOUSING MATERIAL: P - PBT  
N - NYLON

MOUNTING OPTIONS: 3 - PANEL STOPS/EARS & BOARDLOCKS

PORT TYPE: 3 - SINGLE ROW (VERTICAL)

SHIELDING: 0 - NO SHIELD

RIGHT LED COLOR: 0 - NO LED

LEFT LED COLOR: 0 - NO LED